

## Speakers / Passive speakers



	<b>SR15A</b>	<b>SR12A</b>	<b>SR10A</b>	<b>SR15P</b>	<b>SR12P</b>	<b>SR10P</b>
<b>Ref</b>	10159	10158	10157	10270	10269	10268
<b>RMS output</b>	400 W	400 W	300 W	350 W	350 W	250 W
<b>Max output</b>	800 W	800 W	600 W	700 W	700 W	500 W
<b>RMS LF output</b>	350 W	350 W	250 W	300 W	300 W	200 W
<b>RMS HF output</b>	50 W	50 W	50 W	50 W	50 W	50 W
<b>Amp class</b>	D + AB	D + AB	D + AB	-	-	-
<b>Power supply</b>	SMPS	SMPS	SMPS	-	-	-
<b>Protection</b>	Short-circuit, thermal and limiter	Short-circuit, thermal and limiter	Short-circuit, thermal and limiter	-	-	-
<b>Frequency response</b>	40 Hz-20 kHz	45 Hz-20 kHz	55 Hz-20 kHz	45 Hz - 20 kHz	55 Hz - 20 kHz	65 Hz - 20 kHz
<b>H x V dispersion</b>	90° x 60°	90° x 60°	90° x 60°	90° x 60°	90° x 60°	90° x 60°
<b>Cross-over frequency</b>	3.4 kHz	2.8 kHz	2.8 kHz	2.1 kHz	2.1 kHz	2.1 kHz
<b>Sound pressure level (SPL)</b>	124 dB	123 dB max	121 dB max	96 dB max	96 dB max	94 dB max
<b>Woofer</b>	15"x3"	12"x3"	10"x2.5"	15"x3"	12"x3"	10"x2.5"
	4 Ohms	4 Ohms	4 Ohms	8 Ohms	8 Ohms	8 Ohms
	350 W AES	350 W AES	250 W AES	300 W AES	300 W AES	200 W AES
<b>HF driver</b>	1.35"	1.35"	1"	1.35"	1.35"	1"
	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
	50 W RMS	50 W RMS	50 W RMS	50 W RMS	50 W RMS	50 W RMS
<b>Pre-amplification</b>	MIC/LINE input - XLR combo	MIC/LINE input - XLR combo	MIC/LINE input - XLR combo	-	-	-
	XLR line output	XLR line output	XLR line output	-	-	-
	Volume control	Volume control	Volume control	-	-	-
	Equalizer modes: Flat, Live, DJ and Vocal	Equalizer modes: Flat, Live, DJ and Vocal	Equalizer modes: Flat, Live, DJ and Vocal	-	-	-
<b>Housing</b>	2 Monitor-specific angles	2 Monitor-specific angles	2 Monitor-specific angles	2 Monitor-specific angles	2 Monitor-specific angles	2 Monitor-specific angles
	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles
	Installation M10 rigging points	Installation M10 rigging points	Installation M10 rigging points	Installation M10 rigging points	Installation M10 rigging points	Installation M10 rigging points
	36mm socket for speaker stand	36mm socket for speaker stand	36mm socket for speaker stand	36mm socket for speaker stand	36mm socket for speaker stand	36mm socket for speaker stand
<b>Dimensions (H x W x P)</b>	410 x 450 x 710 mm	360 x 400 x 630 mm	310 x 335 x 530 mm	speaker stand	360 x 400 x 630 mm	310 x 335 x 530 mm
<b>Net weight</b>	21.1 kg	19.2 kg	13.4 kg	19.2 kg	17.8 kg	11.8 kg