Speakers / Active speakers



No matter how hard you push the SR12A, it will deliver a very balanced output, and a premium high-definition sound. It can also be used as a monitor speaker and is both very powerful and easy to transport, which means it has an excellent power-to-weight ratio.

2-way self-powered speaker – Bass reflex An ideal sound balance

ref 10158

- + Class D and AB amplifier design 400 W RMS
- + Limiter and equalizer DSP
- + 2 monitor-specific angles



•	Power output : 400 W RMS/800 W Max :
-	350 W RMS Class D LF
6	50 W RMS Class AB HF
•	Switched- mode power supply (SMPS)
•	Frequency response : 20 Hz-20 kHz
•	• HxV Dispersion : 90°x60°
•	Cross-over frequency : 2.8 kHz
•	• SPL : 123 dB max
•	 Speaker : 12"x3[*].4 Ohms , 350 W AES
•	• Driver : 1.35", 8 Ohms, 50 W RMS
•	MIC/LINE input - XLR combo
•	Sortie Line sur XLR
	Volume control
•	Equalizer modes: Flat, Live, DJ and Vocal
•	Protections : short-circuit, thermal and imiter
•	2 Monitor-specific angles
•	1 top and 2 side handles
•	Installation M10 rigging points
	36mm socket for speaker stand

- 36mm socket for speaker stand
- Dimensions : 360 x 400 x 630 mm
- Net weight : 19.2 kg



V-**SR12** Protective cover ref 10168

Protect your speakers from transport and time damages with our high quality covers.

- Strong reinforced construction
 Use your speaker and access its functions while it is cover-protected.
- •Direct access to the transport handles.

221