

Studio sound comes home

A substantial, uncompromising three-way floorstander built to fill even the largest rooms with full-blooded, realistic sound. Powerful bass lines come roaring to life, while the speaker's dedicated Continuum™ midrange driver and Carbon Dome™ tweeter lend an astonishing clarity to vocals and treble effects.

Technical Specifications

Description 3-way vented-box system

Technical features Decoupled Carbon Dome™ tweeter

Continuum[™] cone FST[™] midrange Decoupled midrange

Aerofoil™ Profile bass cones

Flowport™

Drive units 1x ø25mm (1 in) Decoupled Carbon

Dome high-frequency

1x ø150mm (6 in) Continuum cone

FST midrange

2x ø165mm (6.5 in) Aerofoil Profile bass

Frequency range (-6dB) -6dB at 30Hz and 33kHz

Frequency Response -3dB 46Hz - 28kHz ±3dB

Sensitivity 89dB spl (2.83V_{RMS}, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 90Hz - 22kHz <0.5% 120Hz - 20kHz

Nominal impedance 8Ω (minimum 3.1Ω)

Recommended amplifier

power

30W - 200W into 8Ω on unclipped

programme

Dimensions Height: 990mm (39 in) cabinet only

Depth:

1025mm (40.4 in) including plinth

Width: 200mm (7.9 in) cabinet only 320mm (12.6 in) including plinth

300mm (11.8 in) cabinet only

321mm (12.6 in) including grille

and terminals

370mm (14.6 in) including plinth

Net weight 25.0kg (55.2 lb)

Finishes Cabinet: Rosenut

Gloss Black Satin White

Grille: Black

Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST, Aerofoil and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE