



# Electro-Voice

Preliminary



ZX1-Sub

## ZX1-Sub - 12" Subwoofer

- Passive 12" subwoofer delivering outstanding performance
- Ideally suited to both mobile applications and fixed installation
- Tailored to use with ZX1, EVID and EVU compact loudspeaker systems

A range of features make the ZX1-Sub a standout choice in its class. Its EV-engineered 12" EVS-12S woofer operates in the 42 Hz to 200 Hz (-10 dB) frequency range and boasts a frequency response of 53 Hz – 125 Hz (-3 dB). The nominal impedance of the subwoofer is 8 ohms and its maximum sound pressure level is 127 dB. A robust, 15-mm-thick internally braced wooden enclosure with two side handles, a structured coating and a sturdy steel grille

ensure both reliable performance and rugged durability in day-to-day use. The ZX1-Sub's two recessed NL4 type connectors (2) are wired in parallel, permitting the input signal to be looped through and making it possible to operate full-range loudspeakers such as the ZX1 together with the ZX1-Sub using a single amplifier channel. With its compact dimensions (40 x 44 x 46 cm), the latest member of the ZX series weighs-in a just under 20 kilos.

# ZX1-Sub



## Specifications

|                        |  |
|------------------------|--|
| Model No.              | F01U267692   |
| Response: (-3dB)       | 53Hz – 125 Hz  |
| Freq. Range: (-10dB)   | 42 Hz – 200Hz  |
| Rec. Hipass Frequency: | 38 Hz  |
| Axial Sensitivity:     | 94 dB  |
| Max. Measured SPL:     | 127 dB   |
| Coverage:              | Omnidirectional  |
| Power Handling:        | 400W Cont.; 800W Prog.; 1600W Peak                             |
| LF Transducer          | EVS-12S, 305 mm (12") Woofer                                   |
| Nominal Impedance      | 8 $\Omega$   |
| Connectors             | NL4 Type Connector (2)   |
| Enclosure Material:    | 9-ply 15 mm Plywood, internally braced, with textured paint    |
| Grille:                | 16 GA steel with black powdercoat                              |
| Dimensions             | 400mm x 444.5mm x 457.2 mm<br>(15.75 in x 17.50 in x 18.00 in) |
| Net Weight             | 19.8 Kg (43.6lb)   |
| Shipping Weight:       | 25.4 kg (56.0 lb)  |