AMP100.2 MK2

DESCRIPTION

Power amplifier 2x 130Wrms / 4ohm

FEATURES

- Professional 2-channel power amplifier
- This Mk2 version was completely reworked internally for better reliability and higher power
- Extremely compact 19" housing, height only 1U (44mm)
- Lightweight design based on soft start switch mode power supply
- 3 amplifier modes: stereo, mono and bridge
- Power stereo:
 - $2x 130Wrms @ 4\Omega$
 - 2x 70Wrms @ 8Ω
- Power bridge:
 - $1x 260Wrms @ 8\Omega$
- Very efficient cooling, using temperature controlled fans
- Peak limiter prevents signal distortion
- Switchable 75Hz / -24dB low cut filter
- Adjustable input sensitivity: 0,775V ~ 1,0V ~ 1,44V
- Ground lift switch
- A plastic cover (included) can be installed to prevent unauthorized persons from changing the input levels
- DC fault + high temperature + overload and short circuit protections
- Balanced XLR-inputs & jack-outputs: daisy chaining of several amplifiers
- 3 Speakon® outputs: left + right channels + bridge









TECHNICAL SPECIFICATIONS

General : Dimensions (cm) $48.3 \times 24 \times 4.4$

General : Weight (kg) 3.7 **General : Color** black

General : Powerinput AC 240V, 50Hz

General : Energy Label No **General : Display** No

General : Fixation 19" rack mountable

General : RU 1U **General : IP rating** indoor

Audio : frequency range 20 Hz - 20000 Hz

Audio : S/N ratio (> dB) 100 Audio : max. output channels 2 Audio : Wrms 4Ω stereo, per channel 130

channel Audio: Wrms 8Ω stereo, per

channel

Audio : Wrms 8Ω bridge 260

Audio: functions bridge mode, limiter
Connections: input 3 pin XLR, IEC
Connections: output speakon
Brand JB SYSTEMS
EANCode 5420025681278

70



AVOID TAMPERING WITH AUDIO SETTINGS





