

CIRCLE FLAMER X-F1800 SPECIFICATIONS

The CIRCLE FLAMER is the first flamer machine equipped with SHOWVEN's patented rotate nozzle technology, it is a fluid driven flame system with a high accuracy swiveling head, allows for fast and precise flame bursts up to 210° swiveling angles. For easier and convenient use of the machine, it is designed with 88 preset firing sequences.

Features

- Fluid driven flamer system with 210° swiveling angles
- Up to 88 preset firing sequences
- Nozzle front design, safer for operator
- > Safety lock with switchable test mode
- > Stainless steel nozzle, reliable and durable
- > Double electromagnetic valves design for additional safety
- > Double pump ensure stable pressure
- Fitted with igniter signal interface, compatible with fireworks firing system
- ➤ Neutrik powerCON TRUE1 in/out, Neutrik 3-pin & 5-pin DMX in/out
- > Easy effects control with SHOWVEN host controller
- > Stainless steel panel

Specifications

Items	X-F1800
Rotate angle	210°
Preset sequence	88
Flame height	Up to 8-10m (no wind)
Power	380W
Voltage	100-240V, 50-60Hz
Fuel	ISOPAR-G,H,L,M ISOPROPANEL BioEthanol
Fuel bottle capacity	10L
Fuel Consumption	60ml/s
Dimension	590*360*370mm
Net weight	30kg

X-F1800 EFFECTS









