

MT12A-UHF

NEW

The all-inclusive MT self-powered speaker
ref 10286

The MT prestige:

Always as powerful and more innovative. The MT12A-UHF speaker is the latest addition to the MT series. It retains all the qualities and features our reputations was built on: powerful, light and adaptable speakers.

- + Supplied with 2 UHF microphones
- + Class D and AB amplifier
- + 2 inputs Line mic and Line/Aux



Double UHF handheld built-in system :

The MT12A-UHF is supplied with two independent UHF handheld microphones perfectly integrated into the amplification module. The speaker features a preamplifier allowing you to combine the 2 UHF mic with other sources, for professional and public animations or speeches.



Compatible with the CR12 Headset

COV-MT12A

Protective cover

Protect your MT12A-UHF speaker from time and transport damages with the COV-MT12A protective cover

ref 9965



Bi-amplification:

- 250W RMS Class D for LF
- 50W RMS Class AB for HF
- Total power output: 300W RMS / 600W max.

Frequency response: 55 Hz - 20 KHz

Power supply: SMPS

Dispersion H x V: 120° x 60°

Filter cutoff frequency: 2.8 KHz

SPL: 122 dB max.

LF driver:

- 12"
- 2" coil
- 4 Ohms - 250W RMS

HF driver:

- 1.35"
- 8 Ohms
- 50 W RMS

Inputs:

- 1 COMBO XLR/JACK MIC/LINE input

- 1 Mini Jack and Combo XLR/JACK LINE/AUX input

Output: 1 XLR (Master) line output

Settings:

- Settings volume for each channel
- Settings HIGH/LOW +/- 15 dB main

Micro HF:

- UHF diversity with 16 frequencies
- Handheld dynamic cardioid microphone (infrared sync)

Frequency ranges: UHF 863-865 Mhz - 10 mW

Protection: Short-circuit, thermal and limiter

Housing and fixation system:

- 2 monitor-specific angles
- 1 top handle and 2 side handles
- 2 M10 rigging points (below)
- 2 M10 rigging points (on top)
- 36mm mounting plate for a speaker stand

Dimensions: 385 x 348 x 595 mm

Net weight: 16.6 Kg