

Code	Naam
JPR-104-BT	Self-powered desktop monitor set consisting of master and slave, equipment: 4.5"
JPR-104-BTW	Self-powered desktop monitor set consisting of master and slave, equipment: 4.5"
JPR-104BTWH	104-BTW - Self-powered desktop monitor set consisting of master and slave, equipment: 4.5"/0.75" coaxial
jpr-1504	Digital 4-channel amplifier, 1,504 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-1504D	Digital 4-channel amplifier, 1504 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-164	Digital 4-channel amplifier, 160 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-164D	Digital 4-channel amplifier, 160 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-168	Digital 8-channel amplifier, 160 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-168D	Digital 8-channel amplifier, 160 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
JPR-2206H	12", High Power-VGC, Low Freq., 8 Ohm, 600 Watt, 95 dB SPL (1W/1m)
JPR-2226H	15", High Power-VGC, Low Freq., 8 Ohm, 600 Watt, 97 dB SPL (1W/1m)
JPR-2241H	18" High Power Vented Gap Cooling Chassis, 8 Ohm, 600 Watt
JPR-2242H	18" High Power Super Vented Gap Cooling Chassis, 8 Ohm, 800 Watt
JPR-2516	Wall bracket for 8320, 8340A and 8350, rigid, for angle -20°, two parts, only av
JPR-2517	Swivel and tilt wall bracket for 8320, 8340A and 8350
JPR-2520	Rigid wall bracket up to 29 kg, suitable for 9300, 9310, 9320, 9350
jpr-305PMkII	Self-powered5"/1"studiomonitor,41Watt(TT),41Watt(HT),43Hz-24kHz(-10dB),108dBmax.SPLpeak,cross
jpr-306PMkII	Self-powered6.5"/1"studiomonitor,56Watt(TT),56Watt(HT),39Hz-24kHz(-10dB),110dBmax.SPLpeak,cross
jpr-308PMkII	Self-powered8"/1"studiomonitor,56Watt(TT),56Watt(HT),37Hz-24kHz(-10dB),112dBmax.SPLpeak,cross
JPR-3153	Passive or bi-amp 3-way cinema front speaker for small to medium-sized rooms, 4
JPR-3181F	Subwoofer, 18", 4 Ohm, 650 Watt, 132 dB max. SPL (1m), frequency response 30 - 5
jpr-352	Digital 2-channel amplifier, 350 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-352D	Digital 2-channel amplifier, 350 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-354	Digital 4-channel amplifier, 350 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
jpr-354D	Digital 4-channel amplifier, 350 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Power
JPR-3635	Subwoofer, 18" woofer, 8 Ohm, 300 Watt, 100 dB SPL (1W/1m), installation depth:
JPR-3722	2-way screen array system for small rooms, bi-amp operation, 4/8 Ohm LF/HF, 500/
JPR-3722N	2-way screen array system for small rooms, passive operation, 4 Ohm, 400 Watt, 1
JPR-3730	3-way screen array system for small to medium sized rooms, passive or bi-amping,
JPR-3731	3-way screen array system for small rooms and studios, bi-amping,8/8 Ohm, 600 Wa
JPR-3731T	3-Way screen array System for small rooms and studios, Tri-Amping,8/12/8 Ohm, 60
JPR-3732	3-Way screen array System for small to medium sized rooms, bi-amping, 4/8 Ohm, 5
JPR-3732T	3-way screen array system for small to medium sized rooms, tri-amping, 4/8 ohms,
JPR-3733	3-way front system for Samsung Onyx LED screen, mounting above the screen, consi
JPR-3733MK	Mounting plate for 4739 and 3733MHF
JPR-4253	Passive or bi-amp 3-way cinema front speaker for small to medium-sized halls, 4
JPR-4281F	Subwoofer, 2 x 18", 4 or 2x8 Ohm, 1600 Watt, 139 dB max. SPL (1m), frequency res
JPR-4641	Subwoofer, 18" vented gap woofer, 8 Ohm, 600 Watt (2400 Watt peak), 132 dB max.
JPR-4642A	Subwoofer, 2 x 18" vented gap woofer, 4 Ohm, 1.200 Watt (4800 Watt peak), 138 dB
JPR-4645C	Subwoofer, 18" Super Vented Gap woofer, 8 Ohm, 800 Watt (3200 Watt peak), 134 dB
JPR-4722	2-way screen array system for small to medium sized rooms, bi-amp operation, 4/8
JPR-4722N	2-way screen array system for small to medium sized rooms, passive system, 4 Ohm
JPR-4732	3-way screen array system for medium to large rooms, bi-amping,4/4 Ohm, 800 W LF
JPR-4732T	3-way screen array system for medium to large rooms, tri-amping, 4/4/8 ohms, 800
JPR-4HET	4 U, 19" case, deep version for 2x XTi 6000 power amplifiers, 2x lid, 4x butterf
JPR-5628	High-power subwoofer, 2 x 18", 2269H chassis, 4 or 2x 8 Ohm, 4,000 Watt (16,000
JPR-5732	Self-powered 3-way screen array reference system for medium to large rooms and s
JPR-5742	Self-powered 4-way screen array reference system for very large rooms as well as
jpr-702	Digital 2-channel amplifier, 700 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Pow
jpr-702D	Digital 2-channel amplifier, 700 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Pow
jpr-704	Digital 4-channel amplifier, 700 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Pow
jpr-704D	Digital 4-channel amplifier, 700 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Pow
JPR-8102	2-way surround speakers, 10"/1" configuration, 260 Watt, 55 - 18,000 Hz (-10 dB)
JPR-8320	2-way surround system, 8" woofer, 1" titanium tweeter, passive crossover, 110øx9
jpr-84	Digital 4-channel amplifier, 80 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Powe
jpr-84D	Digital 4-channel amplifier, 80 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Powe
jpr-88	Digital 8-channel amplifier, 80 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Powe
jpr-88D	Digital 8-channel amplifier, 80 watts per channel into 4/8 ohms as well as into 70/100 volts, Smart Powe
JPR-9300	2-way surround system, 10" woofer, 1" compression driver, passive crossover, 110

Code	Naam
JPR-9310	2-way surround system, 10" woofer, 1" compression driver, passive crossover, 110
JPR-9320	2-way surround speaker for ceiling or wall mounting, ideal for multitone formats
JPR-9350	3-way high-power surround speaker for ceiling or wall mounting, ideal for multitone
JPR-AC115S	15" Subwoofer 75mm voice coil BLACK
JPR-AC118S	18" Subwoofer 75mm voice coil
JPR-AC15	Ultra-Compact 2-Way speaker, 1 x 5.25" LF. 90° x 90° Coverage, Passive, BLACK
JPR-AC16	Ultra-Compact 2-Way speaker, 1 x 6.5" LF. 90° x 90° Coverage, Passive, black
JPR-AC18/26	Compact 2-Way speaker, 1 x 8" LF. 120° x 60° Coverage, Passive, BLACK
JPR-AC18/95	Compact 2-Way speaker, 1 x 8" LF. 90° x 50° Coverage, Passive, BLACK
JPR-AC195	10" 2-way full-range 90°x50°
JPR-AC195-WH	10" 2-way full-range 90°x50° WHITE
JPR-AC25	Ultra-Compact 2-Way speaker, 2 x 5.25" LF. 90° x 90° Coverage, Passive. BLACK
JPR-AC26	Compact 2-Way speaker, 2 x 6.5" LF. 90° x 90° Coverage, Passive. BLACK
JPR-AC266	Two-Way Full-Range Loudspeaker, 1x12" LF. 60°x60° cov, BLACK
JPR-AC28/26	Compact 2-Way speaker, 2 x 8" LF. 120° x 60° Coverage, Passive. BLACK
JPR-AC28/95	Compact 2-Way speaker, 2 x 8" LF. 90° x 50° Coverage, Passive. BLACK
JPR-AC299	Two-Way Full-Range Loudspeaker, 1x12" LF. 90°x90° coverage, BLACK
JPR-AC566	Two-Way Full-Range Loudspeaker, 1x15" LF. 60°x60° coverage, BLACK
JPR-AC599	Two-Way Full-Range Loudspeaker System, 1x15" LF. 90°x90° coverage, BLACK
JPR-AC895	Two-Way Full-Range Loudspeaker, 1x8" LF. 90°x50° coverage, BLACK
JPR-ACK1	ACK1 - Accessories Caster Kit, caster set for SRX900 subs consisting of 4 pieces 76mm (3") caster wheels
JPR-ADC-H90MKII	Passive 86 cm line array column for horizontal mounting with 6x 4" chassis, 100
JPR-ADC-V90MKII	Passive 86 cm line array column with 6x 4" chassis, 100 Volt transformer with 10
JPR-AL7115	High Power Single 15" Low Frequency Loudspeaker, BLACK
JPR-AM5212/00	2-Way Loudspeaker System, 1x12" LF.100°x100° cov, Bi-amp/passive
JPR-AM5212/26	2-Way Loudspeaker, 1x12" LF. 120°x60° cov, Bi-amp/passive
JPR-AM5212/64	2-Way Loudspeaker, 1x12" LF. 60°x40° cov, Bi-amp/passive
JPR-AM5212/66	2-Way Loudspeaker System, 1x12" LF.60°x60° cov, Bi-amp/passive
JPR-AM5212/95	2-Way Loudspeaker System, 1x12" LF.90°x50° cov, Bi-amp/passive
JPR-AM5215/26	2-Way Loudspeaker, 1x15" LF. 120°x60° coverage, Bi-amp/passive
JPR-AM5215/64	2-Way Loudspeaker, 1x15" LF. 60°x40° coverage, Bi-amp/passive
JPR-AM5215/66	2-Way Loudspeaker, 1x15" LF. 60°x60° coverage, Bi-amp/passive
JPR-AM5215/95	2-Way Loudspeaker, 1x15" LF. 90°x50° coverage, Bi-amp/passive, BLACK
JPR-AM7212/00	High Power 2-Way Loudspeaker,1x12" LF. 100°x100° cov. Bi-amp/pass,BLACK
JPR-AM7212/26	High Power 2-Way Loudspeaker,1x12" LF. 120°x60° cov. Bi-amp/pass,BLACK
JPR-AM7212/64	High Power 2-Way Loudspeaker,1x12" LF. 60°x40° cov. Bi-amp/pass,BLACK
JPR-AM7212/66	High Power 2-Way Loudspeaker,1x12" LF. 60°x60° cov. Bi-amp/pass,BLACK
JPR-AM7212/95	High Power 2-Way Loudspeaker,1x12" LF. 90°x50° cov. Bi-amp/pass,BLACK
JPR-AM7215/26	High Power 2-Way Loudspeaker,1x15" LF. 120°x60° cov. Bi-amp/pass,BLACK
JPR-AM7215/64	2-way system, 15"/1,5" neodymium chassis 2265H and 2432H, 60øx40ø, trapezoidal enclosure
JPR-AM7215/66	High Power 2-Way Loudspeaker,1x15" LF.60°x60° cov.Bi-amp/pass,BLACK
JPR-AM7215/95	High Power 2-Way Loudspeaker,1x15" LF.90°x50° cov.Bi-amp/pass,BLACK
JPR-AM7315/64	High Power 3-Way Loudspeaker, Bi-amp/Tri-amp, 60°x40° cov, BLACK
JPR-ASB6112	Compact High-Power Subwoofer, 2263H 12" Differential Drive®, BLACK
JPR-ASB6115	Compact High-Power Subwoofer, 2265H-1 15" Differential Drive®, BLACK
JPR-ASB6118	High Power Subwoofer.1x18" 2242H SVG Driver. BLACK
JPR-ASB6125	15" High-Power Subwoofer, 2x2265H-1 Differential Drive®, BLACK
JPR-ASB6128	High Power Subwoofer. 2x18" 2242H SVG Driver, Parallel/Disc.
JPR-ASB7118	High-Power 18" Subwoofer, 2269H Differential Drive®, BLACK
JPR-ASB7128	Dual 18" Ultra High-Power Subwoofer, 2 x 2269H Differential Drive®, BLACK
JPR-AW266	High output 12" 2-way full range loudspeaker, 3" voice coil hi drive, WHITE
JPR-AW295	High Power 2-Way All Weather Loudspeaker with 1 x 12" LF & Rotatable Horn, WHITE
JPR-AW526	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF, WHITE
JPR-AW566	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF & Rotatable Horn, WHITE
JPR-AW595	High Power 2-Way All Weather Loudspeaker,1x15" LF,Rotatable Horn, WHITE
JPR-AWC129	All-Weather Compact 2-Way Coaxial Loudspeaker with 12" LF, WHITE
JPR-AWC159	All-Weather Compact 2-Way Coaxial Loudspeaker with 15" LF, WHITE
JPR-AWC159-BK	Weatherproof 2-way system acc. to IP56 according to IEC529, 15"/1" coaxial, ABS
JPR-AWC15LF	All-Weather Compact Low-Frequency Speaker with 15" LF, WHITE

Code	Naam
JPR-AWC15LF-BK	Weatherproof 15" woofer, IP56 according to IEC529, ABS cabinet, 45 Hz - 2.2 kHz
JPR-AWC62	All-Weather Compact 2-Way Coaxial Loudspeaker with 6.5" LF, WHITE
JPR-AWC62-BK	All-Weather Compact 2-Way Coaxial Loudspeaker with 6.5" LF, BLACK
JPR-AWC82	All-Weather Compact 2-Way Coaxial Loudspeaker with 8" LF, WHITE
JPR-C211	Compact 2-way screen array System for small rooms, 15" woofer (M115-8A), 1" tweeter
JPR-C221	Compact 2-way screen array System for small rooms, 15" woofer (M115-8A), 2x 1" tweeter
JPR-C222	2-way screen array System for small and medium-sized rooms, 2x 15" woofer (M115-8A)
JPR-C222HP	2-way screen array System for small and medium-sized rooms, 2x 15" woofer (2275H)
JPR-CBT1000	Jbl CBT 1000 - Line Array Column, BLACK
JPR-CBT1000E	LF Extension for CBT1000 BLACK
JPR-CBT1000E-WH	LF Extension for CBT1000 WHITE
JPR-CBT1000-WH	Constant Beamwidth Technology Adjustable Coverage Line Array Column, WHITE
JPR-CBT100LA	Passive 100 cm line array column with 16x 2" chassis, 325/650/1300 Watt*, 127 dB
JPR-CBT100LA-LS	Line Array Column Loudspeaker, 16 50 mm (2 in) Drivers, EN54:24 cert. BLACK
JPR-CBT100LA-LSWH	Passive 100 cm line array column with 16x 2" chassis, Life Safety Version, EN54
JPR-CBT100LA-WH	Passive 100 cm line array column with 16x 2" chassis, 325/650/1300 Watt*, 127 dB
JPR-CBT200LA	Passive 200 cm line array column with 32x 2" chassis, 650/1300/2600 Watt
JPR-CBT200LA-WH	Passive 200 cm line array column with 32x 2" chassis, 650/1300/2600 Watt
JPR-CBT50LA	Passive 50 cm line array column with 8x 2" chassis, 150/300/600 Watt*, 122 dB
JPR-CBT50LA-LS	Line Array Column Loudspeaker, 8 50mm(2 in) Drivers, EN54:24 Cert. BLACK
JPR-CBT50LA-LS-WH	Line Array Column Loudspeaker, 8 50mm(2 in) Drivers, EN54:24 Cert. WHITE
JPR-CBT50LA-WH	Passive 50 cm line array column with 8x 2" chassis, 150/300/600 Watt*, 122 dB
JPR-CBT70J	Jbl CBT70J - Passive 2-way line array column with 4x 5" TT and 16x 1" HT, 500/1000/2000
JPR-CBT70JE	Low-frequency extension for CBT 70J with 4x 5" TT, 8 Ohm, values with CBT 70J: 1
JPR-CBT70JE-WH	Low-frequency extension for CBT 70J with 4x 5" TT, 8 Ohm, values with CBT 70J: 1
JPR-CBT70J-WH	Passive 70 cm 2-way line array column with 4x 5" TT and 16x 1" HT, 500/1000/2000
JPR-CON126W	Control 126 W - In-wall loudspeaker, 6.5" TT, 1" HT, 100 Watt, 8 Ohm, 88 dB SPL (1 W/1 m), only available in pairs, unit price per pair
JPR-CON126WT	Control 126 WT - In-wall loudspeaker, 6.5" TT, 1" HT, 100/70 Volt version, only available in pairs, unit price per pair
JPR-CON128W	Control 128 W - In-wall loudspeaker, 8" TT, 1" HT, 120 Watt, 8 Ohm, 90 dB SPL (1 W/1 m), only available in pairs, unit price per pair
JPR-CON128WT	Control 128 WT - In-wall loudspeaker, 8" TT, 1" HT, 100/70 Volt version, only available in pairs, unit price per pair
JPR-CON12CT	Control 12C/T - Ceiling loudspeaker, 3" full range chassis, 70/100 Volt switchable 15/7.5/3.8 or 8 Ohm 2
JPR-CON12CTBK	Control 12C/T BK - Ceiling loudspeaker, 3" full range chassis, 70/100 Volt switchable 15/7.5/3.8 or 8 Ohm 2
JPR-CON12CVA	Control 12C-VA - Ceiling loudspeaker, EN54-24 certified, 3" full range chassis, 70/100 Volt switchable 1
JPR-CON14CT	Control 14C/T - Coaxial ceiling loudspeaker, 4" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 25
JPR-CON14CTBK	Control 14C/T BK - Coaxial ceiling loudspeaker, 4" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 25
JPR-CON14CVA	Control 14C-VA - Coaxial ceiling loudspeaker, EN54-24 certified, 4" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 1
JPR-CON16CT	Control 16C/T - Coaxial ceiling loudspeaker, 6.5" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 3
JPR-CON16CTBK	Control 16C/T BK - Coaxial ceiling loudspeaker, 6.5" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 3
JPR-CON16CVA	Control 16C-VA - Coaxial ceiling loudspeaker, EN54-24 certified, 6.5" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable 1
JPR-CON18CT	Control 18CT - Coaxial in-ceiling loudspeaker, 8" woofer, 1" tweeter coaxial, 70/100 Volt switchable 60/30
JPR-CON18CTBK	Control 18CT BK - Coaxial in-ceiling loudspeaker, 8" woofer, 1" tweeter coaxial, 70/100 Volt switchable 60/30
JPR-CON19CS	Control 19CS - Ceiling subwoofer, 8" TT, Nested-Chamber and LDA-Port, sheet steel housing, 180° coverage
JPR-CON19CST	Control 19CST - Ceiling subwoofer, 100 Volt version, 8" TT, switchable 60/30/15 Watt, Nested-Chamber and LDA-Port
JPR-CON1PRO	Control 1 Pro - 2-way near field monitor, including bracket, ball joint on wall plate, 4 Ohm, 150 Watt, 87 dB SPL
JPR-CON1PROWH	Control 1 Pro-WH - 2-way near field monitor, including bracket, ball joint on wall plate, 4 Ohm, 150 Watt, 87 dB SPL
JPR-CON226CT	Control 226CT - Ceiling loudspeaker, 6.5" TT, 1" HT, coaxial, dispersion angle 120°, 47 Hz - 19 kHz, 150 Watt
JPR-CON227C	Control 227C - Ceiling loudspeaker, 6.5" TT, 1" HT, coaxial, dispersion angle 120°, 43 Hz - 19 kHz, 150 Watt
JPR-CON227CT	Control 227CT - Ceiling loudspeaker, 6.5" TT, 1" HT, coaxial, dispersion angle 120°, transformer 70/100 Volt
JPR-CON231	Control 23-1 - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 3" TT
JPR-CON231L	Control 23-1L - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 3" TT
JPR-CON231LWH	Control 23-1L-WH - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 3" TT
JPR-CON231WH	Control 23-1-WH - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 3" TT
JPR-CON24C	Control 24C - Ceiling loudspeaker, 4" TT, 0.75" HT, coaxial, sheet steel bass-reflex housing, 130° radiat
JPR-CON24CM	Control 24C Micro - Ceiling loudspeaker, 2-way system, 4.5" TT, 1/2" HT, sheet steel housing, 30 Watt
JPR-CON24CT	Control 24CT - Ceiling loudspeaker, 100 Volt version, 4" TT, 0.75" HT, coaxial, switchable 30/15/7.5 Watts
JPR-CON24CTBK	Control 24CT black - Ceiling loudspeaker in black, 100 Volt version, 4" TT, 0.75" HT, coaxial, switchable 30/15/7.5 Watts
JPR-CON24CTM	Control 24CT Micro - Ceiling loudspeaker, transformer version 70/100 Volt, 4" TT, 0.75" HT, coaxial, power 30/15/7.5 Watts
JPR-CON24CTMP	Control 24CT Micro Plus - Ceiling loudspeaker, transformer version with 25 Volt, 4" TT, 0.75" HT, coaxial, power 30/15/7.5 Watts
JPR-CON251	Control 25-1 - Compact 2-way system, for indoor and outdoor use (IP-44), incl. InvisiBall wall bracket, 5"

Code	Naam
JPR-CON251L	Control 25-1L - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 5.25"
JPR-CON251LWH	Control 25-1L-WH - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, :
JPR-CON251WH	Control 25-1-WH - Compact 2-way system, for indoor and outdoor use (IP-44), incl. InvisiBall wall bracket
JPR-CON25AV	Control 25AV - Shielded 2-way system, extended frequency range, stainless steel grill, incl. MTC PC, 5
JPR-CON25AVLS	Control 25AV-LS - EN54-24 certified 2-way system for arlamation systems, 5.25" woofer and 0.75" twe
JPR-CON25AVLSWH	Control 25AV-LS-WH - EN54-24 certified 2-way system for laminating systems, 5.25" woofer and 0.75" 1
JPR-CON25AVWH	Control 25AV-WH - Shielded 2-way system, extended frequency range, stainless steel grill, incl. MTC PC
JPR-CON26C	Control 26C - Ceiling loudspeaker, 6.5" TT, 0.75" HT, coaxial, sheet steel bass-reflex housing, 110° disp
JPR-CON26CT	Control 26CT - Ceiling loudspeaker, 100 Volt version, 6.5" TT, 0.75" HT, coaxial, sheet steel bass-reflex
JPR-CON26CTL	Control 26CT-LS - Ceiling loudspeaker, certified according to UL1480 UUMW, 100 Volt version, 6.5" TT
JPR-CON26DT	Control 26DT - Ceiling loudspeaker, 6.5" TT, 0.75" HT, coaxial, 70 Hz - 20 kHz, 100/70 Volt transformer.
JPR-CON281	Control 28-1 - Compact 2-way system, for indoor and outdoor use (IP-44), incl. InvisiBall wall bracket, 8"
JPR-CON281L	Control 28-1L - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, 8" T
JPR-CON281LWH	Control 28-1L-WH - Compact 2-way system, for indoor and outdoor (IP-44), incl. InvisiBall wall bracket, :
JPR-CON281WH	Control 28-1-WH - Compact 2-way system, for indoor and outdoor use (IP-44), incl. InvisiBall wall bracket
JPR-CON29AV	Control 29AV - 2-way system, 300 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x70°, shiel
JPR-CON29AVWH	Control 29AV-WH - 2-way system, 300 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x70°,
JPR-CON2PM	Control 2PM - Self-powered 2-way near field monitor, 2x 35 Watt amplifier, volume control, XLR/jack and
JPR-CON2PS	Control 2PS - 2-way stereo near field monitor set, 1x Master Control 2 PM (active) and 1x Slave (passiv
JPR-CON30	Control 30 - 3-way system, 500 Watt, 4 Ohm low impedance or 100/70 Volt operable, 120°x110°, MF-HF
JPR-CON30WH	Control 30-WH - 3-way system, 500 Watt, 4 Ohm low impedance or 100/70 Volt operable, 120°x110°, M
JPR-CON31	Control 31 - 2-way system, 250 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x110°, 33 - 1:
JPR-CON312CS	Control 312CS - Ceiling subwoofer, 12" TT, rectangular baffle with bass reflex ports, 400 Watt, 8 Ohm, 8
JPR-CON31WH	Control 31-WH - 2-way system, 250 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x110°, 3:
JPR-CON321C	Control 321C - Ceiling loudspeaker, 12" TT, 1" HT, coaxial, dispersion angle 90°, rectangular baffle with
JPR-CON321CT	Control 321CT - Ceiling loudspeakers, 12" TT, 1" HT, coaxial, dispersion angle 90°, rectangular baffle w
JPR-CON322C	Control 322C - Ceiling loudspeaker, 12" TT, 1" HT, coaxial, dispersion angle 90°, rectangular baffle with
JPR-CON322CT	Control 322CT - Ceiling loudspeaker, 12" TT, 1" HT, coaxial, dispersion angle 90°, rectangular baffle wit
JPR-CON328C	Control 328C - Ceiling loudspeaker, 8" TT, 1" HT, coaxial, dispersion angle 100°, round baffle with bass
JPR-CON328CT	Control 328CT - Ceiling loudspeaker, 8" TT, 1" HT, coaxial, dispersion angle 100°, round baffle with bas
JPR-CON40CST	Control 40CS/T - Ceiling subwoofer, 8" TT, bass reflex system, cabinet, integrated passive crossover fo
JPR-CON42C	Control 42C - Satellite ceiling loudspeaker, 2.5" chassis, cabinet, 160° coverage area, 16 Ohm, 30 Watt.
JPR-CON45CT	Control 45CT - Ceiling loudspeaker, 5.5" TT, 1" HT, coaxial, bass reflex housing, 120° dispersion range,
JPR-CON47CT	Control 47C/T - Ceiling loudspeaker, 6.5" TT, 1" HT, coaxial, bass-reflex housing, 120° dispersion range
JPR-CON47HC	Control 47HC - Ceiling loudspeaker with deeper housing for extended frequency range, 6.5" TT, 1" HT, i
JPR-CON47LP	Control 47LP - Ceiling loudspeaker with reduced installation depth, 6.5" TT, 1" HT, coaxial, bass reflex h
JPR-CON50PACK	Control 50PACK - Complete satellite system with 4x Control 52 and 1x Control 50 ST subwoofer for mor
JPR-CON50PACKWH	Control 50PACK-WH - Complete satellite system with 4x Control 52 and 1x Control 50 ST subwoofer for
JPR-CON50ST	Control 50S/T - 8" subwoofer, 100/200/400 Watt, 8 Ohm and 70/100 Volt, 32 - 200 Hz, integrated passiv
JPR-CON50STWH	Control 50S/T-WH - 8" subwoofer, 100/200/400 Watt, 8 Ohm and 70/100 Volt, 32 - 200 Hz, integrated pi
JPR-CON52	Control 52 - Ultra-compact broadband satellite system, with wall bracket, paintable, 2.5" chassis, 140 - 2
JPR-CON52WH	Control 52-WH - Ultra-compact broadband satellite system, with wall bracket, paintable,2.5" chassis, 140
JPR-CON60PST	Control 60PS/T - Pendant subwoofer for suspension from the ceiling, 8" chassis, 150 Watt / 8 Ohm and
JPR-CON62P	Control 62P - Pendant loudspeaker to be suspended from the ceiling, 2.5" full-range system, radiation a
JPR-CON62PWH	Control 62P-WH - Pendant loudspeakeerto be suspended from the ceiling, 2.5" full range system, radiativ
JPR-CON64PT	Control 64P/T - Pendant loudspeaker to be suspended from the ceiling, 4" full range chassis, radiation a
JPR-CON64PTWH	Control 64P/T-WH - Pendant loudspeaker to be suspended from the ceiling, 4" full range chassis, radiati
JPR-CON65PT	Control 65 P/T - Pendant loudspeaker to be suspended from the ceiling, coaxial 2-way system with 5.25
JPR-CON65PTWH	Control 65 P/T-WH - Pendant loudspeaker to be suspended from the ceiling, coaxial 2-way system with
JPR-CON67HCT	Control 67 HC/T - Pendant loudspeaker to be suspended from the ceiling, coaxial 2-way system with 6.5
JPR-CON67HCTWH	Control 67 HC/T-WH - Pendant loud speaker to be suspended from the ceiling, coaxial 2-way system wi
JPR-CON67PT	Control 67 P/T - Pendant loudspeaker to be suspended from the ceiling, coaxial 2-way system with 6.5"
JPR-CON67PTWH	Control 67 P/T-WH - Pendant loudspeaker to be suspended from the ceiling, coaxial 2-way system with
JPR-CON8124	Control 8124 - Ceiling loudspeaker, 4", 130° radiation, 70/100 Volt, power steps at 100 Volt: 6/3/1,5 Watt
JPR-CON8128	Control 8128 - Ceiling loudspeaker, 8", 90° radiation, 70/100 Volt, power steps at 100 Volt: 6/3/1,5 Watt,
JPR-CON8138	Control 8138 - Ceiling loudspeaker, 8", 90° radiation, 70/100 Volt, power steps at 100 Volt: 6/3/1,5 Watt,
JPR-CON85M	Control 85M - Garden loudspeakers in mushroom shape, 2-way system, weatherproof, 5.25" TT / 0.75"
JPR-CON88M	Control 88M - Garden loudspeaker in mushroom shape, 2-way system, weatherproof, 8" TT / 1" HT, 360
JPR-CONCRV	Control CRV - Design loudspeaker in curved form, 2-way, 2x4" TT, 3/4" HT, 75/150/300 Watt, 4 Ohm an

Code	Naam
JPR-CONCRVWH	Control CRV-WH - Design loudspeaker in curved form, 2-way, 2x4" TT, 3/4" HT, 75/150/300 Watt, 4 Ohm
JPR-CONHST	Control HST - Wide-Coverage loudspeaker, 2-way, 5.25" TT / 2x 0.75" tweeters, power handling 100 W
JPR-CONHSTWH	Control HST-WH - Wide-Coverage loudspeaker, 2-way, 5.25" TT / 2x 0.75" tweeters, power handling 100 W
JPR-CONSB2	Control SB2 - 10" bandpass subwoofer, double voice coil, 2x 170 Watt, 2x 8 Ohm, 2x satellite output, black
JPR-CONTROL126W	Premium In-Wall 2-Way speaker, High-Slope Crossover
JPR-CONTROL126WT	Premium In-Wall 2-Way speaker, High-Slope Crossover, with transformer
JPR-CONTROL128W	Premium Quality In-Wall speaker, High Slope Crossover
JPR-CONTROL128WT	Premium Quality In-Wall speaker, High Slope Crossover, with transformer
JPR-CONTROL12C/T	Compact Ceiling speaker 3" (Priced by piece, sold per pair), WHITE
JPR-CONTROL12C/TBK	Ceiling loudspeaker, 3" full range chassis, 70/100 Volt switchable 15/7.5/3.8
JPR-CONTROL12C-VA	3" Compact Ceiling Speaker (Priced by piece, sold per pair)
JPR-CONTROL14C/T	Compact Ceiling speaker 4" (Priced by piece, sold per pair), WHITE
JPR-CONTROL14C/TBK	Coaxial ceiling loudspeaker, 4" woofer, 0.75" tweeter coaxial, 70/100 Volt
JPR-CONTROL14C-VA	2-Way 4" Coaxial Ceilingspeaker (Priced by piece, sold per pair)
JPR-CONTROL16C/T	Compact Ceiling speaker 6.5" (Priced by piece, sold per pair), WHITE
JPR-CONTROL16C/TBK	Coaxial ceiling loudspeaker, 6.5" woofer, 0.75" tweeter coaxial, 70/100 Volt switchable
JPR-CONTROL16C-VA	Two-Way 6.5" Co-axial Ceiling Loudspeaker, EN54-24 Applications
JPR-CONTROL18CT	Coaxial in-ceiling loudspeaker, 8" woofer, 1" tweeter coaxial, 70/100 Volt
JPR-CONTROL18C/TBK	Coaxial ceiling loudspeaker, 8" woofer, 1" tweeter coaxial, 70/100 Volt
JPR-CONTROL19CS	8" In-Ceiling Subwoofer, Long Excursion 200mm(8 in) Driver
JPR-CONTROL19CST	8" In-Ceiling Subwoofer, Long Excursion 200mm(8 in) Driver, with transformer
JPR-CONTROL1PRO	Two-Way Professional Compact Loudspeaker System, BLACK
JPR-CONTROL1PRO-WH	2-way near field monitor, including bracket, ball joint on wall plate, 4 Ohm
JPR-CONTROL226CT	6.5" Coaxial Ceiling Loudspeaker with HF Compression Driver
JPR-CONTROL227C	6.5" Coax Ceiling speaker w/ Compression Driver, 120° Coverage, 150W, 43 Hz to 1
JPR-CONTROL227CT	Ceiling loudspeaker, 6.5" TT, 1" HT, coaxial, dispersion angle 120°, transformer
JPR-CONTROL23-1	Ultra-Compact Indoor/Outdoor Background/Foreground Speaker, BLACK
JPR-CONTROL23-1L	Low impedance Control23-1L (Priced by piece, sold per pair), BLACK
JPR-CONTROL23-1L-WH	Low impedance Control23-1L (Priced by piece, sold per pair), WHITE
JPR-CONTROL23-1-WH	Ultra-Compact Indoor/Outdoor Background/Foreground Speaker, WHITE
JPR-CONTROL24C	Background/ Foreground Ceiling Loudspeakers
JPR-CONTROL24CMICRO	Background Music Ceiling Loudspeaker
JPR-CONTROL24CT	Background/ Foreground Ceiling Loudspeakers, with transformer, WHITE
JPR-CONTROL24CTBLACK	Ceiling loudspeaker in black, 100 Volt version, 4" TT, 0.75" HT, coaxial, switch
JPR-CONTROL24CTMICRO	Background Music Ceiling Loudspeaker, with transformer
JPR-CONTROL24CTMICROPLUS	Ceiling loudspeaker, transformer version with 25 Volt, 4" TT, 0.75" HT, coaxial
JPR-CONTROL25-1	5.25" Two-Way Vented System, Built-In Invisiball mounting, 150W Program, 8 ohms.
JPR-CONTROL25-1L	Low Impedance Control25-1 (Priced by piece, sold per pair), BLACK
JPR-CONTROL25-1L-WH	Low Impedance Control25-1 (Priced by piece, sold per pair), WHITE
JPR-CONTROL25-1-WH	5.25" 2-Way Vented Speaker WH (Priced by piece, sold per pair)
JPR-CONTROL25AV	Compact Indoor/Outdoor Background/Foreground Loudspeaker, BLACK
JPR-CONTROL25AV-LS	EN54-24 certified 2-way system for arlamation systems, 5.25" woofer and 0.75"
JPR-CONTROL25AV-LS-WH	EN54-24 certified 2-way system for laminating systems, 5.25" woofer and 0.75"
JPR-CONTROL25AV-WH	Shielded 2-way system, extended frequency range, stainless steel grill, incl. MT
JPR-CONTROL26C	6.5" Ceiling Loudspeaker Transducer Assembly, 3/4" titanium-coated tweeter
JPR-CONTROL26CT	6.5" Ceiling Loudspeaker Transducer Assembly, 3/4" tweeter, transformer
JPR-CONTROL26CT-LS	Ceiling Loudspeaker Assembly, Life Safety Applications
JPR-CONTROL26DT	Ceiling loudspeaker, 6.5" TT, 0.75" HT, coaxial, 70 Hz - 20 kHz, 100/70 Volt
JPR-CONTROL28-1	High Output Indoor/Outdoor Background/Foreground Speaker, BLACK
JPR-CONTROL28-1L	High-Output 8-Ohm Indoor/Outdoor Back-/Foreground Speaker, BLACK
JPR-CONTROL28-1L-WH	High-Output 8-Ohm Indoor/Outdoor Back-/Foreground Speaker, WHITE
JPR-CONTROL28-1-WH	High Output Indoor/Outdoor Background/Foreground Speaker, WHITE
JPR-CONTROL29AV	2-way system, 300 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x70°
JPR-CONTROL29AV-WH	2-way system, 300 Watt, 8 Ohm low impedance or 100/70 Volt operable, 110°x70°
JPR-CONTROL2PM	Compact Powered Reference Monitor (MASTER)
jpr-Control 2PS	2-way stereo near field monitor set, 1x Master Control 2 PM (active) and 1x Slave (passive), Master equalizer
JPR-CONTROL30	Three-Way High Output Indoor / Outdoor Monitor Speaker, BLACK
JPR-CONTROL30-WH	3-way system, 500 Watt, 4 Ohm low impedance or 100/70 Volt operable, 120°x110°
JPR-CONTROL31	Two-Way High-Output Indoor-Outdoor Monitor Speaker, BLACK

Code	Naam
JPR-CONTROL312CS	12" In-Ceiling Subwoofer. 400 Watts, 30 Hz – 4.5 kHz Frequency Response, 93 dB
JPR-CONTROL31-WH	Two-Way High-Output Indoor-Outdoor Monitor Speaker, WHITE
JPR-CONTROL321C	Premium 12" Coax Ceiling speaker, 90° Coverage. 250 Watts, 34 Hz to 18 kHz, 94
JPR-CONTROL321CT	200 mm (8 inch) Ceiling Speaker Transducer Assembly. Driver, Crossover Network
JPR-CONTROL322C	High-Power 12" Coax Ceiling speaker with Medium Format Compression Driver, 90° C
JPR-CONTROL322CT	Control 322C with pre-attached 100 Watt 70V/100V Multi-Tap Transformer. Taps at
JPR-CONTROL328C	8" Coax Ceiling Speaker with 12" Waveguide. Broadband 120° Coverage. 250 Watts
JPR-CONTROL328CT	Control 328C with pre-attached 60 Watt 70V/100V Multi-Tap Transformer. Taps at
JPR-CONTROL40CS/T	Direct-Radiating In-Ceiling Subwoofer, 8" driver, 30 Hz – 300 Hz, 200W program,
JPR-CONTROL42C	Ultra-Compact Satellite Speaker for use with Control 40CS/T subwoofer. 140 Hz t
JPR-CONTROL45CT	Ceiling loudspeaker, 5.5" TT, 1" HT, coaxial, bass reflex housing, 120°
JPR-CONTROL47C/T	Radiation Boundary Integrator™ technology
JPR-CONTROL47HC	RBI. 75 Watts (at 8? direct setting), plus 60 Watt multi-tap
JPR-CONTROL47LP	Low profile ceiling speaker - JBL Control - 47 LP 120°
JPR-CONTROL50PACK	Packaged Surface-Mount Subwoofer-Satellite Loudspeaker System, BLACK
JPR-CONTROL50PACK-WH	Complete satellite system with 4x Control 52 and 1x Control 50 ST subwoofer
JPR-CONTROL50S/T	Surface-Mount Subwoofer for Subwoofer-Satellite Loudspeaker System, BLACK
JPR-CONTROL50S/T-WH	Surface-Mount Subwoofer for Subwoofer-Satellite Loudspeaker System, WHITE
JPR-CONTROL52	Surface-Mount Satellite Speaker for Subwoofer-Satellite speaker System, BLACK
JPR-CONTROL52-WH	Ultra-compact broadband satellite system, with wall bracket, paintable,2,5"
JPR-CONTROL60PS/T	Pendant Subwoofer with Crossover, BLACK
JPR-CONTROL62P	Mid-high Satellite Pendant Speaker, 2" (50mm) Driver, BLACK
JPR-CONTROL62P-WH	Mid-high Satellite Pendant Speaker, 2" (50mm) Driver, WHITE
JPR-CONTROL64P/T	Comp. Full-Range Pendant Speaker, BLACK
JPR-CONTROL64P/T-WH	Comp. Full-Range Pendant Speaker, WHITE
JPR-CONTROL65P/T	Full range pendant speaker + RBI (Priced by piece, sold per pair). BLACK
JPR-CONTROL65P/T-WH	Full range pendant speaker + RBI (Priced by piece, sold per pair). WHITE
JPR-CONTROL67HC/T	Narrow 75° highceiling speaker+RDI (Priced by piece, sold per pair). BLACK
JPR-CONTROL67HC/T-WH	Narrow 75° highceiling speaker+RDI (Priced by piece, sold per pair). WHITE
JPR-CONTROL67P/T	Extended bass full range + RBI (Priced by piece, sold per pair). BLACK
JPR-CONTROL67P/T-WH	Extended bass full range + RBI (Priced by piece, sold per pair). WHITE
jpr-Control 68HP	Pendant speaker (spherical speaker) for suspension from the ceiling, coaxial 2-way system with 8" and
jpr-Control 68HP-WH	Pendant speaker (spherical speaker) for suspension from the ceiling, coaxial 2-way system with 8" and
JPR-CONTROL8124	Ceiling loudspeaker, 4", 130° radiation, 70/100 Volt
JPR-CONTROL8128	Ceiling loudspeaker, 8", 90° radiation, 70/100 Volt
JPR-CONTROL8138	8inch open back ceiling speaker 70/100V
JPR-CONTROL85M	Two-Way 5.25 inch (135mm) Coaxial Mushroom Landscape Speaker
JPR-CONTROL88M	Two-Way 8 inch (200mm) Coaxial Mushroom Landscape Speaker
jpr-Control 89MS	Garden subwoofer in mushroom shape, 8" chassis, weatherproof, 360° radiation, 150/300 Watt continu
JPR-CONTROLCRV	Curved design, selectable 70V/100V or 4 ohm, indoor/outdoor capable, BLACK
JPR-CONTROLCRV-WH	Curved design, selectable 70V/100V or 4 ohm, indoor/outdoor capable, WHITE
JPR-CONTROLHST	Control HST - Wide coverage On-Wall Speaker, BLACK
JPR-CONTROLHST-WH	Wide-Coverage loudspeaker, 2-way, 5.25" TT / 2x 0.75" tweeters, power handling 1
JPR-CONTROLSB2	Stereo Input Dual Coil Subwoofer
JPR-COVERBOX	Connection box, 42 mm, empty, 2x 16 mm holes, RAL9010, IVX-802105
JPR-COVERBOXXLR	Connection box with 6x XLR, 42 mm, RAL9010, IVX-802120
JPR-CPI2000	5.1 and 7.1 cinema processor; integrated active crossover; presets for JBL cinem
JPR-CRF2	Reflector horn loudspeaker, suitable for LED cinema screens like Samsung Onyx, 2
JPR-CSA1120Z	Single channel 120W output (commercial series) amplifier, built-in 70V and 100V
JPR-CSA1300Z	Single Channel 300W output (commercial series) amplifier, Built-in 70W and 100V
JPR-CSA140Z	Single channel 40W output (commercial series) amplifier, built-in 70V and 100V
JPR-CSA180Z	Single channel 80W output (commercial series) amplifier, built-in 70V and 100V
JPR-CSA2120	Dual Channel 120W output (commercial series) Amplifier
JPR-CSA2120Z	Dual Channel 120W output (commercial series) Amplifier, Built-in 70V and 100V
JPR-CSA2300Z	Dual Channel 300W output (commercial series) amplifier, built-in 70V and 100V
JPR-CSA240Z	JBL CSA240Z _ Dual channel 40W output(commercial series) amplifier, built-in 70V and 100V
JPR-CSA280Z	Dual channel 80W output (commercial series) amplifier, built-in 70V and 100V
JPR-CSM14	4 x 1, mono Public Address mixer
JPR-CSM21	Stereo zone controller with two stereo inputs, microphone and priority input

Code	Naam
JPR-CSM28	8 x 2, 1 x stereo or 2 x mono out Public Address mixer
JPR-CSM32	3 x 2, stereo/mono Public Address mixer
JPR-CSMA1120	Mixing amplifier, 4 Mic/Line inputs on Euroblock and RCA, 1 output on Euroblocks
JPR-CSMA180	Mixing amplifier, 4 Mic/Line inputs on Euroblock and RCA, 1 output on Euroblocks
JPR-CSMA2120	Mixing amplifier, 8 Mic/Line inputs on Euroblock and RCA, 2 output on Euroblocks
JPR-CSMA240	Mixing amplifier, 8 Mic/Line inputs on Euroblock and RCA, 2 outputs on Euroblock
JPR-CSMA280	Mixing amplifier, 8 Mic/Line inputs on Euroblock and RCA, 2 output on Euroblocks
JPR-CSR-2SV-BLK	Wall panel with volume control and 2-way source switching for connection to JBL
JPR-CSR-3SV-BLK	Wall panel with volume control and 3-way source switching for connection to JBL
JPR-CSR-V	Commercial Series Remote Control (V), BLACK
JPR-CSRVLBK	CSR-V - Wall panel with volume control for connection to JBL zone mixer, connection via CAT5 cable ar
JPR-CSS-15C-VA	5" Full Range Ceiling Loudspeaker, EN54-24 Applications
JPR-CSS-1S/T	Two-Way 100V/70V/8-Ohm, 135mm(5.25") LF Loudspeaker, 19mm(.75") tweeter
JPR-CSS8004	100 mm (4 in) Commercial Series Ceiling Speakers
JPR-CSS8008	200 mm (8 in) Commercial Series Ceiling Speakers
JPR-CSS8018	200 mm (8 in) Commercial Series Ceiling Speakers
JPR-CSSBB4X6	Pack of 6 pcs 4" Backcans for CSS8004 Speaker. Steel, zinc-plated, powder-coated
JPR-CSSBB8X6	Pack of 6 pcs 8" Backcans for CSS8008 and CSS8018 Speaker
JPR-CSSH15	15 Watt Paging Horn. Highly weather resistant
JPR-CSSH30	30 Watt Paging Horn. Highly weather resistant
JPR-CSSTR4/8X12	Pack of 12 pcs Tile Rails for CSSBB4 and CSS-BB8 backcan
JPR-CST-2120	70/100 Volt transformer, 2x 120 Watt, for CSA 2120 amplifier, half 19" format
JPR-CWT128	Dual 8" 2-Way Loudspeaker Syst. ft. CWT (Crossfired Waveguide Technology)
JPR-DSILA4	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-DSILA4D	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-DSIMA4	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-DSIMA4D	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-DSISA4	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-DSISA4D	4-channel cinema amplifier, DSP (EQ, X-Over, Limiter, Delay etc.), with presets
JPR-EON208P	Packaged 8" 2-way PA with powered 8-channel mixer and bluetooth audio
JPR-EON210BAGDLX2	Carry Bag Fits 2x EON P210 speakers
JPR-EON610-CVR	Deluxe Padded Cover for EON610
JPR-EON612-CVR-WX	Convertible Cover for EON612 EOL
JPR-EON615-CVR-WX	Weather Resistant Cover for EON615
jpr-EON700 Universal Yoke Mount	PA systems / EON Serie - Accessories EON700 Universal Yoke Mount
JPR-EON700YOKE	EON700 Universal Yoke Mount - Universal U-bracket for EON710, 712, 715 models; weight 2 kg
JPR-EON710	JBL PRO EON710 - 10" Powered PA Speaker with Bluetooth
JPR-EON710BAG	EON710 BAG - Tote Bag for EON710 Speaker
JPR-EON710CVR	EON710-CVR - Transport cover for EON 710, material polyester, lined approx. 10 mm thick, cutout for ti
JPR-EON710CVRWX	EON710-CVR-WX Convertible Cover for EON710 Speaker
JPR-EON712	JBL PRO EON712 - 12" Powered PA Speaker with Bluetooth
JPR-EON712BAG	EON712-BAG - Tote Bag for EON712 Speaker
JPR-EON712CVR	EON712-CVR - Slip On Cover for EON712 Speaker
JPR-EON712CVRWX	JBL EON712-CVR-WX Convertible Cover for EON712 Speaker
JPR-EON715	JBL PRO EON715 - 15" Powered PA Speaker with Bluetooth
JPR-EON715BAG	EON715-BAG - Tote Bag for EON715 Speaker
JPR-EON715CVR	JBL EON715-CVR - Transport cover for EON 715, material polyester, lined approx. 10 mm thick
JPR-EON715CVR(END)	JBL EON715-CVR Convertible Cover for EON715 Speaker
jpr-EON715-CVR-WX	PA systems / EON Serie - Accessories EON715-CVR-WX
JPR-EON715CVRWX	Jbl Eon715 CVR WX - raincover
JPR-EON718S	JBL PRO EON718S - 18" Powered PA Subwoofer
JPR-EON718SCVR	EON718S-CVR - Slip On Cover for EON718S Subwoofer
JPR-EONONECOMPACT	JBL Eon One Compact All-in-One Battery-Powered Portable PA with Professional-Grade Mixer
JPR-EONONECOMPACT512V	USB charging cable for powering external devices (e.g. AKG WMS)
JPR-EONONECOMPACT59V	USB charging cable for powering external devices (e.g. AKG DMS)
JPR-EONONECOMPACTBAG	Jbl Transport bag for EON ONE Compact
JPR-EONONECOMPACTBATT	Rechargeable Lithium-Ion battery for JBL EON Compact
JPR-EONONECOMPACTBP	Backpack for EON ONE Compact, stowable shoulder straps, carrying handle on top
JPR-EONONECOMPACTCHGR	Charger for 2 EON ONE Compact batteries, charging time per battery approx. 3.5 h

Code	Naam
JPR-EONONECOMPACTCVR	Carrying cover for EON ONE Compact, water-resistant 600D nylon fabric
JPR-EONONEMK2	EON ONE MK2 - Compact column PA with rechargeable battery, 8x 2" top and 10" subwoofer, 5-channel PA systems / EON Serie - Accessories EON ONE MK2-BATTERY
jpr-EON ONE MK2-BATTERY	PA systems / EON Serie - Accessories EON ONE MK2-BATTERY-CHARGER
jpr-EON ONE MK2-BATTERY-CHARGER	PA systems / EON Serie - Accessories EON ONE MK2-BATTERY-CHARGER
JPR-EONONEMK2CVR	JBL EON ONE MK-2CVR Cover for EON ONE MK2 Speaker
JPR-EONONEMK2TRANS	EON ONE MK2-TRANSPORTER - 2-piece protective cover for EON ONE MK2 system, consisting of protective hood and subwoofer cover
JPR-EONONEMK2TRANSPORTER	JBL EON ONE MK-TRANSPORTER Transporter for EON ONE MK2 Speaker
JPR-EONONEMKIIBATT	EON ONE MK2-BATTERY - Battery for JBL EON ONE MK2, 36V, Lithium Ion
JPR-EONONEMKIICHGR	EON ONE MK2-BATTERY-CHARGER - Charger for maximum 2 pieces of EON ONE MK2 batteries, charge time approx. 3 hours
JPR-EONONEPRO	Portable, battery-powered linear-array PA system
JPR-EONONEPROTRANSPORTER	2-part protective cover for EON ONE PRO system
JPR-EONONETRANS	EON ONE TRANSPORTER - 2-part protective cover for EON ONE System, consisting of protective hood and subwoofer cover
jpr-GSB12	Weatherproof outdoor subwoofer to be buried in the ground, IP66 certified, placement 12", 117 dB peak
jpr-GSB12TN	Weatherproof outdoor subwoofer for burying in the ground, IP66 certified, 12" placement, 117 dB peak, 30° dispersion
jpr-GSB8	Weatherproof outdoor subwoofer for burying in the ground, IP66 certified, 8" placement; 115 dB peak, 30° dispersion
jpr-GSB8TN	Weatherproof outdoor subwoofer for burying into the ground, IP66 certified, 8" placement, 115 dB peak, 30° dispersion
jpr-GSF3	Weatherproof outdoor speaker, IP56 certified, 2-way system, 3"/1"; 101 dB peak, 80° conical dispersion
jpr-GSF3TN	Weatherproof outdoor speaker, IP56 certified, 2-way system, 3"/1"; 101 dB peak, 80° conical dispersion
jpr-GSF6	Weatherproof outdoor speaker, IP56 certified, 2-way system, 6.5"/1"; 111 dB peak, 70° conical dispersion
jpr-GSF6TN	Weatherproof outdoor speaker, IP56 certified, 2-way system, 6.5"/1"; 111 dB peak, 70° conical dispersion
JPR-HINGEBracket45	Hinge bracket, max. 45ø, RAL9010, IVX-806618
JPR-HINGEBracket90	Hinge bracket, max. 90ø, RAL9010, IVX-802000
JPR-INTELLIVOXDC115	Active DSP line array column, amp bottom, length 115 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDC180	Active DSP line array column, length 180 cm, amp bottom, recommended range up to 25 m, varia
JPR-INTELLIVOXDC280	Active DSP line array column, amp bottom, length 280 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDS115	Active DSP line array column, amp bottom, length 115 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDS180	Active DSP line array column, amp bottom, length 180 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDS280	Active DSP line array column, amp bottom, length 280 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDS430	Active DSP line array column, amp on top, length 430 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDSX180	Active DSP line array column, amp on top, length 180 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDSX380	Active DSP line array column, amp bottom, length 380 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXDSX430	Active DSP line array column, amp on top, length 430 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXPDS170	Active DSP line array column, length 170 cm, recommended range up to 25 m, varia
JPR-INTELLIVOXPDS370	Active DSP line array column, length 370 cm, recommended range up to 50 m, varia
JPR-INTONATO24	24-Ch.Monitor Management Syst.
JPR-INTONATODC	Intonato Desk Top Controller
JPR-IRX108BT	Jbl IRX 108 BT - Haut-parleur portable alimenté de 8" avec Bluetooth
JPR-IRX108BTCVR	IRX108BT-CVR - Carrying case for IRX 108BT, material polyester, lined approx. 10 mm thick, cut-out for mounting
JPR-IRX108BT-CVR	JBL IRX108BT Loudspeaker Cover
JPR-IRX112BT	Jbl IRX112BT - Haut-parleur portable alimenté de 12 "avec Bluetooth
JPR-IRX112BT-CVR	JBL IRX112BT Loudspeaker Cover
JPR-IRX115S	JBL IRX115S - 15" Powered Subwoofer
JPR-IRX115S-CVR	JBL IRX115S Protective Cover for Subwoofer
JPR-IVXBOX42	Cover Box - Connection box, 42 mm, empty, 2x 16 mm holes, RAL9010, IVX-802105
JPR-IVXBOXXL	Cover Box XLR - Connection box with 6x XLR, 42 mm, RAL9010, IVX-802120
JPR-IVXDC115	Intellivox DC115 - Active DSP line array column, amp bottom, length 115 cm, recommended range up to 25 m, varia
JPR-IVXDC180	Intellivox DC180 - Active DSP line array column, length 180 cm, amp bottom, recommended range up to 25 m, varia
JPR-IVXDC280	Intellivox DC280 - Active DSP line array column, amp bottom, length 280 cm, recommended range up to 25 m, varia
JPR-IVXDS115	Intellivox DS115 - Active DSP line array column, amp bottom, length 115 cm, recommended range up to 25 m, varia
JPR-IVXDS180	Intellivox DS180 - Active DSP line array column, amp bottom, length 180 cm, recommended range up to 25 m, varia
JPR-IVXDS280	Intellivox DS280 - Active DSP line array column, amp bottom, length 280 cm, recommended range up to 25 m, varia
JPR-IVXDS430	Intellivox DS430 - Active DSP line array column, amp on top, length 430 cm, recommended range up to 25 m, varia
JPR-IVXDSX180	Intellivox DSX180 - Active DSP line array column, amp on top, length 180 cm, recommended range up to 25 m, varia
JPR-IVXDSX380	Intellivox DSX380 - Active DSP line array column, amp bottom, length 380 cm, recommended range up to 25 m, varia
JPR-IVXDSX430	Intellivox DSX430 - Active DSP line array column, amp on top, length 430 cm, recommended range up to 25 m, varia
JPR-IVXH90	ADC-H90 MkII - Passive 86 cm line array column for horizontal mounting with 6x 4" chassis, 100 Volt transformer
JPR-IVXHINGE90	Hinge Bracket 90° - Hinge bracket, max. 90°, RAL9010, IVX-802000
JPR-IVXHPDS170	Intellivox HP DS170 - Active DSP line array column, length 170 cm, recommended range up to 25 m, varia

Code	Naam
JPR-IVXHPDS370	Intellivox HP DS370 - Active DSP line array column, length 370 cm, recommended range up to 50 m, va
JPR-IVXSWIVEL45	Hinge Bracket 45° - Hinge bracket, max. 45°, RAL9010, IVX-806618
JPR-IVXSWIVEL90	Swivel Bracket 90° - Swivel bracket, max. 90°, RAL9010, IVX-806608
JPR-IVXV90	ADC-V90 MkII - Passive 86 cm line array column with 6x 4" chassis, 100 Volt transformer with 100/50/2:
JPR-IVXWALL25	Wandhalter 25 mm - Rigid wall bracket, distance 25 mm, RAL9010, content 2 pieces, IVX-802225
JPR-IVXWALL35	Wandhalter 35 mm - Rigid wall bracket, distance 35 mm, RAL9010, content 2 pieces, IVX-802235
JPR-IVXWALL60	Wandhalter 60 mm - Rigid wall bracket, distance 60 mm, RAL9010, content 2 pieces, IVX-802260
jpr-JBL EON ONE MK2	Compact column PA with rechargeable battery, 8x 2" top and 10" subwoofer, 5-channel digital mixer, mi
JPR-JRX212	2-way portable stage monitor or FOH speaker with 12" woofer + 1" polymer diaphra
JPR-JRX215	JBL JRX215 - 2-way portable speaker with 15" woofer + 1" polymer diaphragm
JPR-JRX218S	JBL JRX218S - 18" portable subwoofer system, 3" voice-coil woofer
JPR-JRX225	Dual 15" two-way portable speaker system with 2 x 15" woofers + 1" polymer diaphr
JPR-JRX2SYSTEM	Complete system: 2x JRX 212, 2x JRX 218S, 2x Crown XTi 1002 incl. DSP 1x 19"
JPR-LSR305PMKII	JBL 305P MKII - Powered 5" Two-Way Studio Monitor
JPR-LSR305WH	Jbl LSR305 WH - Bi-amplified Studio Monitor,Magnetically-Shielded, 5" woofer, Tweeter
JPR-LSR306PMKII	JBL 306P MKII Powered 6" Two-Way Studio Monitor
JPR-LSR308	Bi-amplified Studio Monitor,Magnetically-Shielded, 8" woofer, Tweeter on Image C
JPR-LSR308PMKII	JBL 308P MKII - Powered 8" Two-Way Studio Monitor
JPR-LSR310S	JBL LSR310S - powered 10" studio subwoofer, 200 Watt Class-D amplifier
JPR-LSR705I	Compact high ouput two-way externally powered studio monitor with 725G five-inch
JPR-LSR705P	JBL LSR705P - 5" Bi-amplified Studio Monitor
JPR-LSR708I	Compact high ouput two-way externally powered studio monitor with 728G eight-inc
JPR-LSR708P	8" Bi-amplified Studio Monitor
JPR-M2	2-Way floor standing or soffit-mount studio reference monitor with very high out
JPR-MTA1	JBL MTA1 Adapter Plate for Wall Bracket
JPR-MTA-21336	Distance rod, height adjustable, 35 mm flange at bottom, 35 mm flange at top
JPR-MTA-21337	Distance rod, height adjustable, M20 flange below, 35 mm flange above
JPR-MTA-24471	Wall bracket up to 15 kg, swivelling up to 180°, tilttable 0°-30°, TSV approved,
JPR-MTA-24481	Wall bracket up to 25 kg, swivelling up to 180°, tilttable 0°-30°, TSV approved,
JPR-MTA-JBL1	Adapter plate for wall bracket 24471 and 24481, hole dimensions 70x127 mm and 50
JPR-MTA-VESA	Adapter plate for wall brackets 24471 & 24481, hole dimension Vesa 100 x100 mm,
JPR-MTC128RIF	Frame for Installing Control 128W to Studs in New Construction. Sold in Pairs,
JPR-MTC200BB6	Back Can for Control 227C&CT Models. Round with Extra-Thick 16-Gauge Steel and
JPR-MTC-210T	70/100 Volt transformer for SB 210, taps 125, 78 and 39 Watt
JPR-MTC210UB	U-Bracket for Control SB-210 Subwoofer, Black.
JPR-MTC210UBWH	Same as MTC-210UB, but in White.
JPR-MTC23CM	Ceiling-Mount Adapter for Control 23, Black. Each Pack Contains 2 Pieces.
JPR-MTC23CMWH	Same as MTC-23, but in White.
JPR-MTC-23UB-1	U-Bracket for Control23-1
JPR-MTC-23UB-1-WH	U-Bracket for Control23-1 WH
JPR-MTC-23WMG-1	WeatherMax grill Control23-1
JPR-MTC-23WMG-1WH	Weather Max Grill for Control 23-1/L, weatherproof to IP-55
JPR-MTC24TR	Trim Ring for Retrofit Installations of Control 24 into Cutouts Up to 250mm (10"
JPR-MTC-25/28CM	Ceiling bracket for Control 25 and Control 28, black
JPR-MTC-25/28CM-WH	Ceiling bracket for Control 25 and Control 28, white
JPR-MTC-25UB-1	U-Bracket for Control25-1
JPR-MTC-25UB-1-WH	U-Bracket for Control25-1 WH
JPR-MTC-25WMG-1WH	Weather Max Grill for Control 25-1/L, weatherproof to IP-55
JPR-MTC26TR	Trim Ring for Retrofit Installations of Control 26 into Cutouts Up to 250mm (10"
JPR-MTC-28H	Bracket for horizontal mounting of two Control 28 (120°), 3x MTC 28H make 360
JPR-MTC-28UB-1	U-Bracket for Control28-1
JPR-MTC-28UB-1-WH	U-Bracket for Control28-1 WH
JPR-MTC-28WMG-1	WeatherMax grill Control28-1
JPR-MTC-28WMG-1WH	Weather Max Grill for Control 28-1/L, weatherproof to IP-55
JPR-MTC29CM	Ceiling-Mount Adapter for Control 29AV, Black. Each Pack Contains 2 Pieces.
JPR-MTC29CMWH	Same as MTC-29CM, but in White.
JPR-MTC29UB	U-Bracket for Control 29AV.
JPR-MTC29UBWH	Same as MTC-29UB, but in White.
JPR-MTC2P	Wall-Mount Bracket Kit for Control 2P. Includes Two Wall Mounts, One Power Supp

Code	Naam
JPR-MTC300BB12	Best-in-Class Three Cubic Foot Back Box for 12" Models. Rectangular with Extra-
JPR-MTC300BB8	One Cubic Foot Back Box for 8" Models. Round with Extra-Thick 16 Gauge Metal an
JPR-MTC300SG12	Contemporary Square Grille for 12" Models. Fashionable Upscale Look, White, Met
JPR-MTC300T150	150 Watt Transformer for Higher Output from a 70V or 100V System. Use with Non-
JPR-MTC30CM	Ceiling-Mount Adapter for Control 30, Black. Each Pack Contains 2 Pieces.
JPR-MTC30CMWH	Same as MTC-30CM, but in White.
JPR-MTC30UB	U-Bracket for Control 30.
JPR-MTC30UBWH	u bevestiging voor control 30 wit
JPR-MTC81BB8	Pre-Install Backcan, large 7.4 liter volume, 7" H x 11¾" dia, 11½" mounting circ
JPR-MTC-81TB8	Metal installation frame for pre-installation in ceilings, suitable for Control
JPR-MTC-CBT-70T	70/100 Volt transformer for CBT 70J, taps at 120/60/30 Watt
JPR-MTCCBTFM1	Flush Mount wall bracket for CBT50LA-1/CBT100LA-1
JPR-MTCCBTFM1WH	Same as above but in white
JPR-MTCCBTFM2	Jbl MTC CBT FM2 - Flush Mount wall bracket for CBT70J-1/CBT70JE-1
JPR-MTCCBTFM2WH	Same as above but in white
JPR-MTCCBTSMB1	Stand-Mount Bracket for CBT
JPR-MTC-CBT-SUS3	Suspension Bracket for CBT Speakers
JPR-MTC-CBT-SUS3-WH	Suspension Brackets for CBT Speakers WHITE
JPR-MTCP2	Panel Cover Provides Liquid-Tight Sealed Entrance for Input Terminal, also funct
JPR-MTC-PC3	Sealed Panel Cover side entry (2 pcs) (Price is for a package of two covers)
JPR-MTCSB2W	Bracket for Installing Control SB-2 to Wall or Corner.
JPR-MTU1	U-Bracket For Models AM6215 (/95 or /64) and AM4215 (/95 or /64)
JPR-MTU15	U-Bracket For Model AC15
JPR-MTU16	U-Bracket For Model AC16
JPR-MTU18	U-Bracket For Models AC18/95 & AC18/26
JPR-MTU-2	U-bracket for AC 2215 / 95/64/00
JPR-MTU25	U-Bracket For Model AC25
JPR-MTU26	U-Bracket For Model AC26
JPR-MTU-266-99	U-Bracket for AC266 and 299, b
JPR-MTU28	U-Bracket For Models AC28/95 & AC28/26
JPR-MTU3	U-Bracket For Models AM6212 (/95, /64 or /00) and AM4212 (/95, /64, or/00).
JPR-MTU4	U-Bracket For Model AC2212 (/95, /64, or /00).
JPR-MTU-566-99	U-Bracket for AC566 and 599, b
JPR-MTU-895	U-Bracket for AC895, black
JPR-MTU-9320	U-bracket for surround speaker 9320
JPR-PD5122	2 x 12" subwoofer
JPR-PD525S	High Output, Dual 15" Low-Frequency / Subwoofer Loudspeaker
JPR-PD544	15" Horn-Loaded Full-Range Loudspeaker System
JPR-PD564	15" Horn-Loaded Full-Range Loudspeaker System
JPR-PD595	15" Horn-Loaded Full-Range Loudspeaker System
JPR-PD6212-64	Horn loaded high performance loudspeaker, 12" woofer, 1,5" tweeter, 60°x40°
JPR-PD6212-66	Horn loaded high performance speaker, 12" woofer, 1,5" tweeter, 60°x60°
JPR-PD6212-95	Horn loaded high performance speaker, 12" woofer, 1,5" tweeter, 90°x50°
JPR-PD6322-43	Horn loaded high performance speaker, 2x 12" woofer, 8" CMCD midrange driver
JPR-PD6322-66	Horn loaded high performance speaker, 2x 12" woofer, 8" CMCD midrange, 1,5"
JPR-PD6322-95	Horneladener Hochleistungs-Lautsprecher, 2x 12" Tieftöner, 8"CMCD Mitteltöner
JPR-PROGRAMMIER-SET	Programming Set USB w/5-pin XLR, IVX-386602
JPR-PRX412M	JBL PRX412M 12" Two-Way Stage Monitor and Loudspeaker System
JPR-PRX412MCVR	Padded Nylon Cover for PRX412M
JPR-PRX415M	15" 2-way stage monitor or FOH speaker passive speaker, 1200W peak power handlin
JPR-PRX415MCVR	Padded Nylon Cover for PRX415M
JPR-PRX415M-WH	2-weg 15 inch passieve speaker/monitor, 1200W, 8ohm
JPR-PRX418S	Jbl Prx418s - 18" portable subwoofer system, 35Hz freq range, 2400W peak
JPR-PRX418SCVR	Padded Nylon Cover for PRX418S
JPR-PRX425	Dual 15" 2-way FOH speaker passive speaker, 2400W peak power handling, 134dB SPL
JPR-PRX4SYSTEM	Complete system: 2x PRX 412M, 2x PRX 418S, XTi 2002 with DSP (Tops), XTi 4002
JPR-PRX618SCVR	Gevoerde beschermingshoes voor PRX618S, zwart
JPR-PRX715XLFCVR	Deluxe Padded cover for PRX715-XLF
JPR-PRX718XLF	High performance powered portable 18" subwoofer, extended low frequency, 1500W c

Code	Naam
JPR-PRX812W	JBL PRX812W - 12" Two-Way Full-Range Main System/Floor Monitor with Wi-Fi
JPR-PRX815W	JBL PRX815W 15" Two-Way Full-Range Main System and Floor Monitor with Wi-Fi
JPR-PRX815XLFW	JBL PRX815XLFW - 15" Self-Powered Extended Low-Frequency Subwoofer System
JPR-PRX815XLFWCVR	JBL Deluxe Padded Cover for PRX815XLF Speaker (Black)
JPR-PRX818XLFW	JBL PRX818XLFW 18" Self-Powered Extended Low-Frequency Subwoofer System
JPR-PRX825W	JBL PRX825W Dual 15" Two-Way Full-Range Main System with Wi-Fi
JPR-PRX835W	JBL PRX835W 15" Three-Way Full-Range Main System with Wi-Fi
JPR-PRX908	JBL PRX908 - Professional Powered Two-Way 8-inch PA Loudspeaker
jpr-PRX908-BAG	PA systems / PRX900 Series - Accessories PRX908-BAG
jpr-PRX908-CVR	PA systems / PRX900 Series - Accessories PRX908-CVR
jpr-PRX908-CVR-WX	PA systems / PRX900 Series - Accessories PRX908-CVR-WX
JPR-PRX912	JBL PRX912 - Professional Powered Two-Way 12-inch PA Loudspeaker
jpr-PRX912-BAG	PA systems / PRX900 Series - Accessories PRX912-BAG
JPR-PRX912-CVR	PA systems / PRX900 Series - Accessories PRX912-CVR
jpr-PRX912-CVR-WX	PA systems / PRX900 Series - Accessories PRX912-CVR-WX
JPR-PRX915	JBL PRX915 - Professional Powered Two-Way 15-inch PA Loudspeaker
jpr-PRX915-BAG-W	PA systems / PRX900 Series - Accessories PRX915-BAG-W
jpr-PRX915-CVR	PA systems / PRX900 Series - Accessories PRX915-CVR
jpr-PRX915-CVR-WX	PA systems / PRX900 Series - Accessories PRX915-CVR-WX
JPR-PRX915XLF	JBL PRX915XLF - 15" Self-Powered Extended Low Frequency Subwoofer System with Wi-Fi
JPR-PRX915XLF-CVR	PA systems / PRX900 Series - Accessories PRX915XLF-CVR
JPR-PRX918XLF	JBL PRX918XLF - Professional Powered 18-inch Subwoofer
jpr-PRX918XLF-CVR	PA systems / PRX900 Series - Accessories PRX918XLF-CVR
JPR-PRXONE	JBL PRX ONE - ALL-IN-ONE POWERED COLUMN PA WITH MIXER AND DSP
JPR-PSB-1	Stereo soundbar, full range from 42 - 20,000 Hz, 2" TT, 0.75 HT, 2x 20 Watt
JPR-SB2210	2x 10" subwoofer, plastic housing, 500/2.000 Watt power handling
JPR-SB2210-WH	2x 10" subwoofer, plastic housing, 500/2.000 Watt power handling
JPR-SCS12	2-way coaxial surround speaker for ceiling or wall mounting, ideal for multitone
JPR-SCS8	2-way coaxial surround speaker for ceiling or wall mounting, ideal for multitone
jpr-SLP12/T-BK	Flat wall speaker with 15° forward tilted baffle, incl. wall mount, 3" full range driver, 130°x130° dispersior
jpr-SLP12/T-WH	Flat wall speaker with baffle inclined 15° to the front, incl. wall bracket, 3" full range chassis, 130°x130° c
jpr-SLP14/T-BK	Flat wall speaker with 15° forward tilted baffle, incl. wall mount, 4" full range driver, 140°x140° dispersior
jpr-SLP14/T-WH	Flat wall speaker with 15° forward tilted baffle, incl. wall mount, 4" full range driver, 140°x140° dispersior
JPR-SRX812	Jbl SRX812 - 12" Two-Way Bass Reflex Passive System
JPR-SRX812P	JBL SRX812P - 12" Powered Two-Way, Fully configurable DSP including 20 PEQs, 96kHz FIR Filters
JPR-SRX812P-CVR-DLX	Deluxe Padded Cover
JPR-SRX815	15" Two-Way Bass Reflex Passive System
JPR-SRX815P	Jbl SRX815P - 15" Powered Two-Way, Fully configurable DSP including
JPR-SRX815PCVRDLX	Deluxe Padded Cover for SRX815P
JPR-SRX815P-CVR-DLX	Deluxe Padded Cover
JPR-SRX818S	JBL SRX818S - 18" Passive Subwoofer System
JPR-SRX818SP	JBL SRX818SP - Single 18"powered sub 2000W
JPR-SRX818SP-CVR-DLX	Deluxe Padded Cover
JPR-SRX818SP-CVR-DLX-WK4	Transport cover suitable for JBL SRX818SP with mounted wheels
JPR-SRX828P	Jbl Srx828p - Dual 18" Powered subbass, Fully configurable DSP
JPR-SRX828PCVRDLX	Deluxe Padded Cover for SRX828SP
JPR-SRX828S	18" Dual Passive Subwoofer System
JPR-SRX828SP	JBL SRX828SP - Dual 18"powered sub 2000W
JPR-SRX828SP-CVR-DLX	Transport cover for SRX828SP, material 1000-D Nylon, lined approx. 10 mm thick
JPR-SRX828SP-CVR-DLX-WK4	Transport cover suitable for JBL SRX828SP with mounted wheels
JPR-SRX835	15" Three-Way Bass Reflex Passive System
JPR-SRX835P	Jbl SRX835P - Powered Three-Way, Fully configurable DSP
JPR-SRX835PCVRDLX	Padded Nylon Cover for SRX835p
jpr-SRX900LA AF	Flying frame for SRX910LA, consisting of 2 parts, carries up to 16x SRX910LA (depending on safety fac
JPR-SRX900LAPB	SRX900LA PB - pull-back accessory for SRX906/910LA, for max. 16 elements
JPR-SRX900RC	SRX900 RC - Rain cover for display, audio and data connectors, fits all SRX900 models
JPR-SRX906LA	JBL PRO SRX906LA Dual 6.5-inch Powered Line Array Loudspeaker
JPR-SRX906LAAF	SRX906LA AF - Flying frame for SRX906LA, consisting of 2 parts, carries up to 16x SRX906LA (dependen
JPR-SRX906LABP	SRX906LA BP - Base plate for groundstack applications, max. 6x SRX906LA, -15° to +5° adjustable, M:

Code	Naam
JPR-SRX906LA CASE	SRX906LA Case - Flightcase for 4x SRX906LA, handles, wheels
JPR-SRX910LA	JBL PRO SRX910LA Dual 10-inch Powered Line Array Loudspeaker
JPR-SRX910LAAF	SRX910LA AF - Flying frame for SRX910LA, consisting of 2 parts, carries up to 16x SRX910LA (depends on configuration)
JPR-SRX910LABP	SRX910LA BP - Base Plate for groundstack applications, max. 4 pcs. SRX910LA, -15° to +5° adjustable
JPR-SRX910LAVT	SRX910LA VT - Vertical Transporter for 4x SRX910LA, consisting of rolling board and lid
JPR-SRX910LAVTCVR	SRX910LA VT CVR - Cover for 4x SRX910LA on dolly, lined nylon, zipper, cutouts on handles, flaps balanced
JPR-SRX918S	JBL PRO SRX918S 18-inch Powered Subwoofer
JPR-SRX918SCVR	SRX918S CVR - Cover for SRX918S, lined nylon, cutouts on handles
JPR-SRX928S	JBL PRO SRX928S Dual 18-inch Powered Subwoofer
JPR-SRX928SCVR	SRX928S CVR - Cover for SRX928S, lined nylon, cutouts on handles
JPR-SUB18	18" Studio Subwoofer
JPR-SWIVELBRACKET90	Swivel bracket, max. 90°, RAL9010, IVX-806608
JPR-USB-RS485	USB RS485 converter, IVX-387802
JPR-VLA-C2100	2-way, Full Range Line-Array Loudspeaker, 100°
JPR-VLA-C215S	2x 15" subwoofer, suitable addition to VLA-C2100/C265, 2x 15", chassis 2267H
JPR-VLA-C265	2-Way, Full Range Line-Array Loudspeaker, 65°
JPR-VMA1120	Mixer/Amplifier 5ch. 120W
JPR-VMA1120EU	VMA 1120 - ELA mixer amplifier, 5x inputs, 1x output zone, 120 watts at 4, 8 ohms as well as at 70/100 volt
JPR-VMA1240	Mixer/Amplifier, 5x input channel, 240W
JPR-VMA1240EU	VMA 1240 - ELA mixer amplifier, 5x inputs, 1x output zone, 240 watts at 4, 8 ohms as well as at 70/100 volt
JPR-VMA160	Mixer/Amplifier 5 ch. 60W
JPR-VMA160EU	VMA 160 - ELA mixer amplifier, 5x inputs, 1x output zone, 60 watts at 4, 8 ohms as well as at 70/100 volt
JPR-VMA2120	Mixer/Amplifier 8ch. 120W
JPR-VMA2120EU	VMA 2120 - ELA mixer amplifier, 8x inputs, 2x output zones each 120 watts at 4, 8 ohms and at 70/100 volt
JPR-VMA260	Mixer/Amplifier 8ch.80W
JPR-VMA260EU	VMA 260 - ELA mixer amplifier, 8x inputs, 2x output zones each 60 watts at 4, 8 ohms as well as at 70/100 volt
JPR-VRX10SYSTEM	Complete system: 4x VRX 932LAP, 4x VRX 918SP, 2x distance rods MTA21337
JPR-VRX915M	15" 2-way floor monitor, 800 watt 2265H woofer, 2452H, 4" voice coil driver, 50W
JPR-VRX915S	15" compact, flying subwoofer; 2265G-1 800 W AES
JPR-VRX915SGRILLE	Grille VRX915S 363892-001
JPR-VRX915SWH	800W 15" bass-reflex subwoofer, WHITE
JPR-VRX918S	18" compact, flying subwoofer; 2268H woofer, integral flying hardware compatible
JPR-VRX918SP	Powered 18" flying subwoofer, 2268H Differential Drive LF, Crown DPC-2 amplifier
JPR-VRX918SWH	18" Compact, Flying Subwoofer; 2268H woofer; Integral Flying Hardware Compatible
JPR-VRX928GRILLE	Grille VRX928 363541-001
JPR-VRX928LA	8" 2-way line-array system with 1 x 2168H-1 400 W woofer, 2 x 2414H
JPR-VRX928LAWH	8" 2-way line-array system with 1 x 2168H-1 400 W woofer, 2 x 2414H
JPR-VRX932LA	12" Two-Way line-array system
JPR-VRX932LAP	Powered 12" two-way line-array system with 1 x 2262H, BLACK
JPR-VRX932LA-WH	12"/3x 1" line array, neodymium-plated, 75 Hz - 20 kHz, 100°x15°, 800/1600/3200W
JPR-VRX9SYSTEM	Complete system: 4x VRX 928LA, 2x VRX 915S, 2x Crown XTi 2002 with DSP
JPR-VRXAF	Array Frame for suspending VRX932LA-1/P, VRX918S/P enclosures. Includes 4 x Quick Release pins
JPR-VRXSMAF	Small Array Frame for suspending VRX928LA and VRX915S arrays. Includes 2 x quick release pins
JPR-VT4883	2x 12" subwoofer (2263H-1), flying, cardioid possible, NL4 and NL8 connections
JPR-VT4886	Passive 3-way line array, 12 Ohm, 2x 6.5" DCD woofer, 4x 2.5" midrange driver
JPR-VT4886-AF	Flying frame for VT 4886 and VT 4883, groundstack suitable, Aluminium, black, 21"
JPR-VT4886-SF	Compact flying frame for VT 4886, aluminium, black
JPR-VTXA12	Large 3-way line array with 2x12", tri-amp, RBI waveguide, 45 Hz - 19 kHz, 1,400W
JPR-VTXA12AF	Flying frame for VTX A12 line array elements
JPR-VTXA12SB	Suspension Bar, compact hanging arm for A12 elements, ideal as pull-back
JPR-VTXA12VT	Vertical transporter (dolly) for 4x A12
JPR-VTXA12VTCVR	VTX A12 cover for 4x A12 on Vertical Transporter (Dolly)
JPR-VTXA12W	Large 3-way line array "Wide" with 2x12", tri-amp, RBI waveguide, 45 Hz - 19 kHz
JPR-VTXA6	JBL VTX A 6 Sub-Compact Dual 6.5" Line Array Element
JPR-VTXA6BP	JBL VTX A 6 BP Base Plate for A6
JPR-VTXA6CASE	JBL VTX A 6 CASE Road Case for (4) VTX A6
JPR-VTXA6CM	JBL VTX A 6 CM Ceiling Mount Accessory for A6 and B15
JPR-VTXA6MF	JBL VTX A 6 MF Mini Frame for A6 and B15
JPR-VTXA6SB	JBL VTX A 6 SB Suspension Bar for A6 and B15

Code	Naam
JPR-VTxb15	JBL VTX B15 Compact Arrayable 15-inch Subwoofer
JPR-VTxb15ACC	JBL VTX B15 ACC Accessory Cover & Caster Board
JPR-VTxb15G	JBL VTX B15G Compact 15" Subwoofer
JPR-Vtxf12	Multifunctional high-power loudspeaker, 12"/1.5" neodymium-plated, D2 tweeter
JPR-Vtxf15	Multifunctional high-power loudspeaker, 15"/1,5" Neodymium components
JPR-Vtxf18S	High-power subwoofer, 18"(2269H) neodymium-plated, NL4 connectors front and rear
JPR-Vtxf35/64	High-power front system, 3-way system, 2x15"/8"/1.5" neodymium chassis
JPR-Vtxg28	High-power subwoofer 2x 18" (2269H), 22 - 160 Hz, 4.000 Watt, 2x 8 Ohm
JPR-Vtxg28-ACC	Accessory kit for VTX G28, dolly and protective cover, sold only as a package
JPR-Vtxm20	High-power stage monitor, 2-way system, 2x 10"/1,5" neodymium chassis 2261H
JPR-Vtxm22	High-power stage monitor, 2-way system, 2x 12"/1,5" neodymium chassis 2262H
JPR-Vtxpm	JBL VTX PM Universal 35 mm Pole Mount adapter, T-Bar style
JPR-Vtxs25	High-power 2x 15" subwoofer ( 2267H ), flyable, 28 - 400 Hz, 4.000 Watt
JPR-Vtxs25-Vt	VTX S25 vertical transporter for 3x S25
JPR-Vtxs25-Vtcvr	VTX S25 cover for 3x S25
JPR-Vtxs28	High-power 2x 18" subwoofer ( 2269H ), flyable, 24 - 400 Hz, 4000 Watt, 2x 8 Ohm
JPR-Vtxs28-ACC	Accessory kit for VTX S28, dolly and protective cover, sold only as a package
JPR-Vtxv20	3-Way Line Array with HF Waveformer, drive bi-amp or tri-amp, RBI Waveguide
JPR-Vtxv20-Af	Flying frame for VTX V20 and S25, groundstacking also possible, steel, black
JPR-Vtxv20-Afeb	Extention bar to complement the VTX V20-AF flying frame, steel, black
JPR-Vtxv20-Pb	Pull back for JBL VTX V20
JPR-Vtxv20-Vt	VTX V20 vertical transporter for 4x V20
JPR-Vtxv20-Vtcvr	VTX V20 cover for 4x V20
JPR-Vtxv25	3-Way Line Array with HF Waveformer, RBI Waveguide, 35 Hz - 20 kHz, 4000 LF/1400
JPR-Vtxv25-ACC	Accessories kit for VTX V25, dolly and protective cover, sold only as a package
JPR-Vtxv25-Af	JBL VTX V25 array frame
JPR-Vtxv25-Afeb	JBL VTX V25 array frame extension bar
JPR-Vtxv25-Pb	JBL VTX V25 pull back
jpr-Wall bracket 25 mm	Rigid wall bracket, distance 25 mm, RAL9010, content 2 pieces, IVX-802225
jpr-Wall bracket 35 mm	Rigid wall bracket, distance 35 mm, RAL9010, content 2 pieces, IVX-802235
jpr-Wall bracket 60 mm	Rigid wall bracket, distance 60 mm, RAL9010, content 2 pieces, IVX-802260
JPR-Wandhalter25mm	Rigid wall bracket, distance 25 mm, RAL9010, content 2 pieces, IVX-802225
JPR-Wandhalter35mm	Rigid wall bracket, distance 35 mm, RAL9010, content 2 pieces, IVX-802235
JPR-Wandhalter60mm	Rigid wall bracket, distance 60 mm, RAL9010, content 2 pieces, IVX-802260
LEX-PCM NATIVE EFFECTS BUNDLE	Software Plug-Ins PCM Native Effects Bundle
LEX-PCM NATIVE TOTAL BUNDLE	Software Plug-Ins PCM Native Total Bundle