Contest® 🌢

ANU-6X

DMX command panel

6 universal channels

- + 6-channel DMX command panel
- + 6 faders + Master
- + Can be operated with a battery



TECHNICAL SPECIFICATIONS

6-channel DMX command panel 6 faders + Master Can be operated with a 9V battery AC adaptator supplied Perfect for architectural colour changer lightings DMX output: 3-pin XLR Dimensions : 173 x 153 x 55 mm Weight: 0.8 kg

PPILOT

DMX command panel

Colour and program management. Up to 4 projectors simultaneously

138

Command panel

Simplified universal remote control compatible with a large number of CONTEST® products*

ref 8701

- + Direct access to colours and elaborate scenes
- + Adjustable scene speed
- + Manual, auto and musicsensitive modes



TECHNICAL SPECIFICATIONS

2-control modes: Fixed colours and sequences 4 or 16 DMX channels 10 built-in programs Music-sensitive + Tap Tempo modes and colour variations Fast access to the 8 fixed colours Adjustable speed and intensity Strobe effect: 16 flashes per second Fast or progressive colour sequencing Black out Power supply: 12 V 100 mA, DC (supplied) Dimensions: 70 x 110 x 33 mm Weight: 0.31 kg Compatible with the LED4 STAGE and the Contest® LED PAR products



TECHNICAL SPECIFICATIONS

Connectors: Jack 6.35 stéréo

Cable length: 11 m

* Compatible with:

LED-BLASTER, LED-OMEGA, LED-SPIDER, LED-STAR, LED-SUPRA, LED-GUN,

SCN830, NINO, LE CLUB series