ROTOGOBO ZOOM


DESCRIPTION

A powerful logo projector based on a 50W cold white led

FEATURES

- A powerful logo projector based on a 50W cold white led.
- Low gobo temperature: no need for expensive heat resistant metal or glass gobos!
- Four FREE metal gobos included: [Sale, Happy New-Year, Presents, Hearts]
- Uses standard metal gobos and glass gobos.
- Can also be used with plastic film gobos that can be produced by a standard laser printer!
 - (Gobo templates and instructions available on our website)
- Adjustable beam angle: 20° to 34°
- Adjustable focus.
- Different working modes:
 - **Standalone:** Manual settings for dimmer, strobe and rotation (with IR-remote).
 - **Master/slave mode:** several projectors can be used together for synchronized projections.
 - **DMX-controlled:** 1, 2, 3 or 4 channel mode.
- Infrared remote control included.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE! (Briteq® order code: B04645)
- 2x 8 alphanumeric LED-display for easy menu navigation.
- Very low noise operation: can be used in shops and showrooms.







TECHNICAL SPECIFICATIONS

General : Dimensions (cm) $50 \times 15 \times 10$

General: Weight (kg) 2.77

General : Powerinput AC 100 - 240V, 50/60Hz

General: Energy Label No
General: Power consumption W 56
General: Color black
General: Display LCD
General: IP rating indoor

Control : Modes standalone fixed, standalone automatic, manual, DMX, DMX

Master/Slave

Control: Protocol DMX, Wireless DMX

Control : manual Yes
Control : Master/Slave Yes
Control : SMART-DMX No

Control : Standalone automatic, fixed **Control : Type included remote** Wireless IR remote

Control: programmable
Control: upgradable software
Control: maximum DMX channels
Light: lamp socket
Light: lamp
Light: colors
Cold white

Light : mix colors No

Light : functions manual focus, manual zoom

Light: min. beam angle (°) 20 Light: max. beam angle (°) 34 Light: max. refresh rate (kHz) No

Connections : input3 pin XLR, wireless DMX optional,

PowerCon® or compatible 3 pin XLR, PowerCon® or

Connections : output compatible

Brand JB SYSTEMS

EANCode 5420025651660







