

Visit product page



# **IBP-INTERCOM BELTPACK**

#### L006211

Professional single channel intercom wired belt pack, 2-Wire / Party Line Belt Pack, Talk and Call button, Volume control, XLR-3 loop through connector, XLR-4F headset connector, sidetone adjustment, full-duplex communication, clear and loud communication sound, easy operation, and strong noise resistance. Dimensions 10.5 x 8.7 x 4.8cm.

#### **TECHNICAL DETAILS**

#### **Product description**

Intercom beltpack, with plastic housing, desing to operate with the IMS (master station) and IEH (intercom headset). Offers stable and reliable performance, flexible configuration, with full duplex with clear and loud communication.

#### **Technical Specifications**

## Microphone Amplifier (From Microphone to Line)

- Dynamic Headset Microphone impedance: 200 ohm Voltage Gain: 44±3dB
- Harmonic Distortion :< 1% (1000Hz)

#### Headphone Amplifier (From Line to Load)

- Load impedance: 50-600 ohm Voltage Gain: 31±3dB
- Harmonic Distortion :< 2% (1000Hz)

### **Power Requirements**

- 24V DC, 60mA±10mA
- Power Range: 15-30V DC

Environmental conditions for operation:-10~55°C

## **PHOTOS**

















